

Title (en)

CYLINDER FOR A ROTARY PRINTING MACHINE

Publication

EP 0132532 B1 19860910 (DE)

Application

EP 84105957 A 19840525

Priority

DE 3326215 A 19830721

Abstract (en)

[origin: US4510868A] To support a cover wrapped about the printing cylinder and prevent oscillations and resonance phenomena from arising when an attachment groove (2, 23) passes along an adjacent cylinder, a filler strip (8) is located within the groove to close off the groove. The filler strip has circumferentially extending fingers (14) which are supported on circumferentially extending fingers (15) projecting circumferentially from within the groove. The filler strip is axially shiftable along the fingers so that the gap between the support fingers (15) can be used to drop the comb fingers (14) on the filler strip radially inwardly, thus retracting the filler strip. The filler strip is preferably retracted by a retracting mechanism such as a slotted guide tube (11) engaging a lifting strip (10) projecting circumferentially from the filler strip. Axial shifting of the filler strip to place the comb fingers of the filler strip above the support fingers (15) projecting from the groove, after raising of the filler strip, to be flush with the circumference of the cylinder is effected by an eccentrically positioned drive located, for example, at an end face of the cylinder. The arrangement permits use of rubber blankets which have end portions fitting in a tiny gap between the filler strip and the groove, with the rubber blankets having ends fitting precisely against each other, thus providing an essentially continuous surface to an engaging cylinder.

IPC 1-7

B41F 27/12; B41F 7/22

IPC 8 full level

B41F 27/12 (2006.01); **B41F 27/14** (2006.01); **B41F 30/00** (2006.01); **B41F 30/04** (2006.01)

CPC (source: EP US)

B41F 27/125 (2013.01 - EP US); **B41F 27/1293** (2013.01 - EP US); **B41F 30/04** (2013.01 - EP US)

Cited by

EP0280141A3; EP0280159A3; EP0807521A1; DE19537420C1; US5749299A

Designated contracting state (EPC)

CH DE FR GB IT LI SE

DOCDB simple family (publication)

EP 0132532 A1 19850213; EP 0132532 B1 19860910; DE 3326215 A1 19850207; DE 3326215 C2 19860403; DE 3460685 D1 19861016;
JP H0430910 B2 19920525; JP S6038156 A 19850227; US 4510868 A 19850416

DOCDB simple family (application)

EP 84105957 A 19840525; DE 3326215 A 19830721; DE 3460685 T 19840525; JP 14705984 A 19840717; US 63007884 A 19840712