

Title (en)

PLUGGABLE PIN GROUP FOR MAKING AN ADJUSTABLE ELECTRICALLY CONDUCTING CONNEXION TO AN ELECTRICAL OUTLET

Publication

EP 0133561 A3 19850327 (DE)

Application

EP 84109264 A 19840804

Priority

IT 8344183 A 19830805

Abstract (en)

[origin: EP0133561A2] The plug has its contact pins either in a longitudinal or transverse direction. Each pin sits in a hole open on two orthogonal sides to provide two entrances 90 degrees apart. The holes are at appropriate places in the plug's two-part casing. Each pin is fixed into a seating block inside the casing. The block fits into the casing in either of two positions to allow the pin to project from either one of the two holes in the casing. Each block has a blank projection to block off the unused hole. The casing halves are disconnected by unscrewing a screw, separated and the blocks changed in position. The casing halves are then screwed together again.

IPC 1-7

H01R 13/56

IPC 8 full level

H01R 13/56 (2006.01)

CPC (source: EP)

H01R 13/567 (2013.01)

Citation (search report)

- [X] DE 3135781 A1 19830324 - HIRSCHMANN RADIOTECHNIK [DE]
- [A] FR 1307518 A 19621026 - DANFOSS VED INGENIPHIR MADRS CL
- [A] DE 2240331 A1 19731108 - CONTACT GMBH
- [A] FR 977146 A 19510328 - COMP GENERALE ELECTRICITE

Cited by

DE3918517C1

Designated contracting state (EPC)

AT BE CH DE FR GB LI LU NL SE

DOCDB simple family (publication)

EP 0133561 A2 19850227; EP 0133561 A3 19850327; EP 0133561 B1 19870107; AT E24798 T1 19870115; BR 8403932 A 19850709; DE 3461968 D1 19870212; ES 290661 U 19861216; ES 290661 Y 19870801; GR 80037 B 19841211; IT 1209045 B 19890710; IT 8383441 A0 19830805; MX 158083 A 19890105

DOCDB simple family (application)

EP 84109264 A 19840804; AT 84109264 T 19840804; BR 8403932 A 19840806; DE 3461968 T 19840804; ES 290661 U 19840806; GR 840180037 A 19840806; IT 8344183 A 19830805; MX 20228384 A 19840806