

Title (en)

DEVICE FOR TUCKING-IN THE WEFT ENDS IN A LOOM

Publication

EP 0134377 B1 19861126 (DE)

Application

EP 83810397 A 19830901

Priority

EP 83810397 A 19830901

Abstract (en)

[origin: US4565225A] A blower nozzle is provided on the shot or weft insertion side of the weaving machine for blowing the severed end of the weft thread into an eyelet of a selvedge-tucking needle. By transferring the weft thread end by means of the blower nozzle, a particularly short time within the operating cycle of the weaving machine is required for the procedure of transferring the weft thread end to the selvedge-tucking needle. This permits higher operating speeds of the weaving machine.

IPC 1-7

D03D 47/48

IPC 8 full level

D03D 47/48 (2006.01)

CPC (source: EP US)

D03D 47/48 (2013.01 - EP US)

Cited by

EP1696061A2; EP0778364A3; EP0483067A1; EP1512782A3; EP0351361A1; US4984608A; EP0562213A1; US5316050A; EP0340165A1; US4901769A; US7124782B2

Designated contracting state (EPC)

BE CH DE FR GB IT LI

DOCDB simple family (publication)

EP 0134377 A1 19850320; EP 0134377 B1 19861126; BR 8404351 A 19850903; CS 249521 B2 19870312; DE 3367942 D1 19870115; IN 165741 B 19900106; JP H0447053 B2 19920731; JP S6071741 A 19850423; SU 1382406 A3 19880315; US 4565225 A 19860121

DOCDB simple family (application)

EP 83810397 A 19830901; BR 8404351 A 19840831; CS 654684 A 19840830; DE 3367942 T 19830901; IN 591CA1984 A 19840827; JP 17854584 A 19840829; SU 3786919 A 19840830; US 64254284 A 19840820