

Title (en)
LEAD-THROUGH INSULATORS, ESPECIALLY FOR REFRIGERATING MACHINES

Publication
EP 0134390 B1 19870616 (DE)

Application
EP 84103204 A 19840323

Priority
DE 3324466 A 19830707

Abstract (en)
[origin: US4700999A] A current leadthrough particularly for a refrigerator comprises an insulator with a plurality of electrically conductive spaced apart pins extending through the insulator. The insulator includes a disc-shaped base portion with a plurality of nub portions corresponding to the member of pins, the pins extending through the nub portions. The nub portions extending upwardly from the base portion and the base portion comprise a material having temperature stability which is insensitive to chemicals and has some elasticity.

IPC 1-7
H01B 17/26; **H01R 13/52**

IPC 8 full level
H01B 17/26 (2006.01); **H01B 17/30** (2006.01); **H01R 13/52** (2006.01)

CPC (source: EP US)
H01B 17/306 (2013.01 - EP US); **H01R 2201/10** (2013.01 - EP US)

Designated contracting state (EPC)
AT FR GB IT NL

DOCDB simple family (publication)
US 4700999 A 19871020; AT E27871 T1 19870715; AU 2883184 A 19850110; AU 575325 B2 19880728; BR 8402894 A 19850521; CA 1221752 A 19870512; DE 3324466 A1 19850117; DE 3324466 C2 19860828; DK 161115 B 19910527; DK 161115 C 19911118; DK 331984 A 19850108; DK 331984 D0 19840706; EP 0134390 A1 19850320; EP 0134390 B1 19870616; ES 278942 U 19840916; ES 278942 Y 19850401; IN 161126 B 19871010; JP H03121629 U 19911212; JP S6037614 A 19850227; TR 21912 A 19851101

DOCDB simple family (application)
US 89447286 A 19860804; AT 84103204 T 19840323; AU 2883184 A 19840530; BR 8402894 A 19840613; CA 458286 A 19840706; DE 3324466 A 19830707; DK 331984 A 19840706; EP 84103204 A 19840323; ES 278942 U 19840418; IN 339CA1984 A 19840516; JP 13925284 A 19840706; JP 255491 U 19910130; TR 2191284 A 19840704