

Title (en)

Sewing of panty hose on a transfer machine with a plurality of cooperating turrets.

Title (de)

Nähen von Strumpfhosen auf einer Transfemaschine die aus mehreren, einander folgenden Karussells besteht.

Title (fr)

Couture de collants sur une machine transfert comportant une succession de carrousels.

Publication

**EP 0136391 A1 19850410 (FR)**

Application

**EP 83830182 A 19830922**

Priority

EP 83830182 A 19830922

Abstract (en)

Equipment for stitching up the ends of the legs of a pair of tights incorporates a pair of rotating turrets of which one (A1) supports several pairs of horizontal suction tubes (3) which collect the legs of basic tubular tights fabricated by an adjacent machine (T). Twin pairs of prong jaws (6) extend the waistband of the stocking body to a rectangular form large enough to allow the body to be inverted about the outside of the tubes containing the legs. The legs are inverted so that as the first turret steps through its rotation, the ends of the legs are presented respectively to one of two conventional units (8) for trimming and stitching the toe ends. A further multiple jaw carriage (B2) similar to that (B1) which transferred the stocking body from (T) to (A1) then transfers the stocking body to supports (31) on the second turret (A2) where the gusset region of the body is stiffened and, if necessary, cut open, before presenting the tights to a conventional machine (5) for stitching the gusset, opt. via an intermediate transfer device (G).

Abstract (fr)

La machine comporte 4 carrousels successifs T,A1,A2,S. 2 jeux de 4 doigts expaneurs (B1,B2) saisissent la ceinture, la conforment en rectangle et la tirent par dessus un des bras (30) (31) du carrousel, suivant en rebroussant le collant chaque fois. A1, dont les bras (30) sont aspirants, présente les pieds du collant à une machine à coudre CP. A2 étire la région périénale pour la présenter à un dispositif (35) de découpe de l'ouverture du soufflet. Un dispositif (G) saisit les bords de cette ouverture pour la présenter au carroussel S où le soufflet est préparé et cousu.

IPC 1-7

**D05B 35/00**

IPC 8 full level

**A41B 11/14** (2006.01); **D05B 23/00** (2006.01)

CPC (source: EP US)

**D05B 23/007** (2013.01 - EP US); **D05D 2207/04** (2013.01 - EP US); **D05D 2303/20** (2013.01 - EP US)

Citation (search report)

- [AD] EP 0070813 A1 19830126 - SOLIS SRL [IT]
- [Y] GB 2081316 A 19820217 - MORI SUKEO
- [Y] FR 2415684 A1 19790824 - CHIETTI GIOVANNI [IT]
- [A] US 3520262 A 19700714 - BOLLES JAMES CHADBOURN, et al
- [Y] GB 2103257 A 19830216 - SAVIO & C SPA [IT]
- [A] FR 2508506 A1 19821231 - SOLIS SRL [IT]

Cited by

FR2793815A1; CN110904578A; US4953687A; EP0533637A1; US5272993A; CN110512358A; EP0306460A1; CN110512367A; WO0071799A1

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

**EP 0136391 A1 19850410; EP 0136391 B1 19870422**; CA 1200800 A 19860218; DE 3371099 D1 19870527; JP H0243517 B2 19900928;  
JP S6080484 A 19850508; US 4649838 A 19870317

DOCDB simple family (application)

**EP 83830182 A 19830922**; CA 438666 A 19831007; DE 3371099 T 19830922; JP 18715583 A 19831007; US 53585683 A 19830926