

Title (en)
Metal teeming seals.

Title (de)
Metall-Ausguss-Dichtungen.

Title (fr)
Joints pour la coulée de métal.

Publication
EP 0136733 A1 19850410 (EN)

Application
EP 84201089 A 19840724

Priority
GB 8321585 A 19830810

Abstract (en)
A seal at a junction between a refractory nozzle 2 dependent from a vessel containing a molten metal charge and a tubular shroud 3 for enveloping the molten metal during teeming, comprising a pliable ring gasket (7 or 8) sandwiched between the nozzle and the shroud, the gasket containing or consisting of a material designed to soften at the operating temperature experienced at said junction sufficient to assume a shape and attitude such as to seal any voids.

IPC 1-7
B22D 11/10; **B22D 41/08**

IPC 8 full level
B22D 41/50 (2006.01)

CPC (source: EP)
B22D 41/502 (2013.01)

Citation (search report)
• [A] US 3877675 A 19750415 - SHAPLAND JAMES T
• [A] DE 2919880 A1 19801127 - DIDIER WERKE AG
• [A] US 4165026 A 19790821 - HAZLEHURST IAN J, et al
• [A] DE 2625742 A1 19761223 - CENTRE RECH METALLURGIQUE
• [A] DE 2743312 A1 19790329 - DIDIER WERKE AG

Cited by
EP0759415A4; DE19758071C1; DE19757802C1; EP0282247A1; FR2635283A1

Designated contracting state (EPC)
BE CH DE FR IT LI NL SE

DOCDB simple family (publication)
EP 0136733 A1 19850410; ES 534964 A0 19850516; ES 8505461 A1 19850516; GB 2144662 A 19850313; GB 2144662 B 19860828; GB 8321585 D0 19830914; GB 8419955 D0 19840912

DOCDB simple family (application)
EP 84201089 A 19840724; ES 534964 A 19840808; GB 8321585 A 19830810; GB 8419955 A 19840806