

Title (en)
GAS-DISCHARGE ARRESTER AND FABRICATION METHOD

Publication
EP 0138082 B1 19880127 (DE)

Application
EP 84111068 A 19840917

Priority
DE 3335602 A 19830930

Abstract (en)
[origin: US4665337A] For the reduction of the work function of the electrodes, gas discharge arresters contain an activator which contains, for example, an alkali metal or nickel. Getter materials, for example barium aluminum, serve the purpose of gettering of gases which can arise in the surge voltage arrester during manufacture or during operation. With these substances, the spreads of the minimum operating voltage can be maintained small as long as the activator is only moderately heated. For high loads, the activator contains an alkali metal or nickel and, in addition, barium aluminum, whereby tungsten and/or molybdenum is present as the additional substance. An activator of this type guarantees constant values of the minimum operating voltage and a narrow spread of these values even after a high electrical and thermal load. A frequent switching of the maximally permissible current is possible without an interfering alteration of the electrical characteristics.

IPC 1-7
H01T 1/22

IPC 8 full level
H01J 9/44 (2006.01); **H01J 17/04** (2006.01); **H01T 1/20** (2006.01); **H01T 1/22** (2006.01); **H01T 4/00** (2006.01)

CPC (source: EP US)
H01T 1/22 (2013.01 - EP US)

Cited by
US5671114A; DE19632417C1; EP0242688A1; US4739439A; EP0242590B1; EP0700589B1

Designated contracting state (EPC)
CH DE FR GB LI SE

DOCDB simple family (publication)
EP 0138082 A1 19850424; **EP 0138082 B1 19880127**; DE 3335602 A1 19850418; DE 3469119 D1 19880303; JP H0223996 B2 19900528; JP S6095875 A 19850529; US 4665337 A 19870512

DOCDB simple family (application)
EP 84111068 A 19840917; DE 3335602 A 19830930; DE 3469119 T 19840917; JP 20394184 A 19840928; US 65195884 A 19840919