

Title (en)
METHOD FOR MAKING A PARQUET FROM END GRAIN WOOD BLOCKS

Publication
EP 0139660 B1 19881019 (FR)

Application
EP 84900844 A 19840224

Priority
• BE 210213 A 19830225
• BE 212111 A 19831223

Abstract (en)
[origin: WO8403321A1] A parquet is made from end grain wood blocks (1) which are fixed to a resilient slab (2) by gluing the lower face (4) of each of the blocks by means of an elastic glue (6). The edges in contact with the support are softened so as to avoid tearing the support and the edges on the facing side are bevelled to conceal the possible interstices between adjacent blocks and obtain a surface continuity effect. Prefabricated laying elements are obtained by assembling the blocks on an adhesive width cut to the required dimensions and applied to the facing side.

IPC 1-7
E04F 15/022; **E04F 15/16**; **E04F 15/22**

IPC 8 full level
E04F 15/022 (2006.01); **E04F 15/16** (2006.01); **E04F 15/22** (2006.01)

CPC (source: EP)
E04F 15/022 (2013.01); **E04F 15/043** (2013.01); **E04F 15/166** (2013.01); **E04F 15/22** (2013.01)

Cited by
US2011030300A1

Designated contracting state (EPC)
AT BE CH DE FR GB LI LU NL SE

DOCDB simple family (publication)
WO 8403321 A1 19840830; DE 3474705 D1 19881124; EP 0139660 A1 19850508; EP 0139660 B1 19881019; IT 1173383 B 19870624; IT 8419807 A0 19840227

DOCDB simple family (application)
BE 8400004 W 19840224; DE 3474705 T 19840224; EP 84900844 A 19840224; IT 1980784 A 19840227