

Title (en)

Device for applying adhesives.

Title (de)

Auftragsgerät für Klebstoff.

Title (fr)

Dispositif pour l'application d'adhésifs.

Publication

**EP 0140136 A1 19850508 (DE)**

Application

**EP 84111193 A 19840919**

Priority

DE 3337878 A 19831018

Abstract (en)

1. An applicator for a liquid composition comprising a chassis (1) which can be driven by means of wheels (5), with at least one container holder (2) for fixing at least one container (3) for the liquid composition (6) wherein the container holder (2) is adjustable between a readiness position in which the outlet opening (4) of the container (3) runs horizontally or is directed upwardly and an application position in which the outlet opening (4) runs vertically downwards or obliquely downwards, the chassis having a bearer (8), in particular a profiled bearer on which the container holder (2) is fixed, characterised in that several adhesive container holders (2) can be fixed detachably independently of one another and are arranged transversely or perpendicularly to the direction of travel of the applicator in moveable and fixable manner as well as next to one another on the bearer (8) of the applicator provided for applying adhesive (6), in particular for applying prepolymer adhesive based on polyurethane for fixing insulating materials on light roof constructions, in such a way that, in the readiness position, the adhesive outlet openings of all adhesive containers (3), in particular adhesive bottles, fixed in the adhesive container holders (2) run horizontally or are directed upwards and that, in the adhesive application position, the adhesive outlet openings of all these adhesive containers (3) run vertically downwards or are directed obliquely downwards.

Abstract (de)

Mit der Erfindung wird ein Auftragsgerät für Klebstoff, insbesondere zum Auftragen von Prepolymerkleber auf Polyurethanbasis zur Fixierung von Dämmmaterialien auf Leichtdachkonstruktionen zur Verfügung gestellt, das ein Fahrgestell (1) mit wenigstens einer Klebstoffbehälterhalterung (2) zum lösbaren Befestigen von wenigstens je einem Klebstoffbehälter (3) umfaßt, wobei vorzugsweise die Klebstoffbehälterhalterung (2) einen starr am Fahrgestell (1) anbringbaren Halterungssträger (25) und einen relativ zu letzterem zwischen einer Bereitschafts- und einer Klebstoffauftragsposition verschwenkbaren Klebstoffbehälterträger (8) aufweist.

IPC 1-7

**B05C 5/00; E04D 15/06**

IPC 8 full level

**B05C 5/00 (2006.01); E04D 15/06 (2006.01); E04D 15/07 (2006.01)**

CPC (source: EP)

**B05C 5/00 (2013.01); E04D 15/07 (2013.01)**

Citation (search report)

- [A] FR 2464331 A1 19810306 - BOLLAG MOSES [CH]
- [A] DE 2559848 B1 19790705 - DEBUSCHEWITZ KG H
- [A] DE 2828324 A1 19800110 - CARSTEDT HOWARD B

Cited by

DE19600009C1; EP0401124A1; DE3928897C1; CN105133797A; EP0620325A1; DE3734510A1; US7896200B2; WO2006132428A1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

**EP 0140136 A1 19850508; EP 0140136 B1 19870429; AT E26805 T1 19870515; DE 3337878 A1 19850425; DE 3463345 D1 19870604**

DOCDB simple family (application)

**EP 84111193 A 19840919; AT 84111193 T 19840919; DE 3337878 A 19831018; DE 3463345 T 19840919**