

Title (en)  
TAMPON PRINTING MACHINE

Publication  
**EP 0140165 B1 19880713 (DE)**

Application  
**EP 84111505 A 19840927**

Priority  
DE 3335230 A 19830929

Abstract (en)  
[origin: US4557195A] A pad-type printing machine with a mount for a cliché, with an ink supply device exhibiting a hollow body, whereby during the operation of the machine the end face of the hollow body rests at least occasionally on the cliché, with a device for pressing the end face of the hollow body against the cliché, with a device for producing a relative motion between the cliché and the hollow body, whereby the hollow body is guided such that it can swivel about an axis extending basically parallel to the relative motion, and with a pad which can be pressed onto the inked cliché and which accepts the ink from the recesses in the cliché and transfers it onto an object to be printed is characterized by the fact that at least on some of the circumference of its end face the hollow body comprises hard material and is microfinished with a peak-to-valley height of at most 2  $\mu$  m whereby the device for pressing the hollow body against the cliché is designed such that the contact force acts in the immediate vicinity of the contact surface between the cliché and the hollow body and is at least approximately uniformly distributed over the circumference of the end face, whereby the hollow body is guided such that it can additionally swivel about an axis extending transversely to the relative motion between the cliché and the hollow body. This permits a high working speed with only little outlay on maintenance. (FIG. 1).

IPC 1-7  
**B41F 31/00**; **B41F 17/14**

IPC 8 full level  
**B41F 17/34** (2006.01); **B41F 17/00** (2006.01); **B41F 17/14** (2006.01); **B41F 31/00** (2006.01)

CPC (source: EP US)  
**B41F 17/001** (2013.01 - EP US)

Cited by  
DE202012007064U1; DE4129946A1; DE102010041522B4; EP0347762A3; DE19908864A1; BE1004736A3; DE19908847A1; US5832835A; EP0472021A1; CN100378913C; DE4312727C2; DE19908849A1; EP0537649A1; EP2366547A1; DE3737937A1; US4905594A; DE3744979C2; EP0568133A1; US5363761A; WO2005081286A1; EP2433797A1; DE102010041522A1; US8490544B2

Designated contracting state (EPC)  
BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)  
**EP 0140165 A2 19850508**; **EP 0140165 A3 19851121**; **EP 0140165 B1 19880713**; DE 3335230 A1 19850411; DE 3335230 C2 19910307; DE 3472647 D1 19880818; JP H036911 B2 19910131; JP S60143963 A 19850730; US 4557195 A 19851210

DOCDB simple family (application)  
**EP 84111505 A 19840927**; DE 3335230 A 19830929; DE 3472647 T 19840927; JP 20547884 A 19840929; US 65419584 A 19840924