

Title (en)  
SAFETY LOCK

Publication  
**EP 0140740 B1 19870624 (FR)**

Application  
**EP 84401820 A 19840913**

Priority  
• FR 8314789 A 19830916  
• FR 8314790 A 19830916

Abstract (en)  
[origin: ES8505759A1] The present invention relates to a safety lock including a cylindrical body in which is movably mounted a cylinder containing a safety mechanism which is constituted by pivoting blades meshing respectively with toothed wheels loosely mounted on an axis pin transversely connected to a cylinder and each provided with a notch adapted to be positively and drivingly connected to a catch for operating the lock mechanism, only after the notches are caused to coincide with the catch which initially is spaced from the wheels.

IPC 1-7  
**E05B 29/00**; **E05B 17/14**

IPC 8 full level  
**E05B 17/18** (2006.01); **E05B 29/00** (2006.01)

CPC (source: EP US)  
**E05B 17/186** (2013.01 - EP US); **E05B 29/002** (2013.01 - EP US); **Y10T 70/7576** (2015.04 - EP US); **Y10T 70/7627** (2015.04 - EP US); **Y10T 70/7633** (2015.04 - EP US); **Y10T 70/7667** (2015.04 - EP US); **Y10T 70/7684** (2015.04 - EP US); **Y10T 70/7695** (2015.04 - EP US); **Y10T 70/7712** (2015.04 - EP US)

Cited by  
EP0552595A1; EP0428029A3; FR2701988A1

Designated contracting state (EPC)  
AT BE CH DE GB IT LI NL SE

DOCDB simple family (publication)  
**EP 0140740 A1 19850508**; **EP 0140740 B1 19870624**; DE 3464396 D1 19870730; ES 535950 A0 19850601; ES 8505759 A1 19850601; PT 79197 A 19841001; PT 79197 B 19860717; US 4601184 A 19860722

DOCDB simple family (application)  
**EP 84401820 A 19840913**; DE 3464396 T 19840913; ES 535950 A 19840914; PT 7919784 A 19840913; US 64912284 A 19840910