

Title (en)

METHOD OF INCREASING THE DEGREE OF SEPARATION IN A CYCLONE, AND CYCLONE FOR CARRYING OUT SAID METHOD

Publication

EP 0141073 B1 19891129 (DE)

Application

EP 84109299 A 19840806

Priority

SE 8304429 A 19830816

Abstract (en)

[origin: US4606739A] The separating efficiency of a cyclone separator used for removing solid particles from a gas stream (for example ash particles from the combustion gas which is passed to a gas turbine) is increased by retarding the particles before they arrive at the cyclone and thereafter accelerating them over a short distance before they enter the cyclone. In this way large particles will have a lower speed than small particles when entering the cyclone. Despite a high velocity of the transport gas and a high inlet velocity for small particles, it is possible to obtain an inlet velocity for larger particles which is desirably low from the point of view of reducing erosion of the cyclone separator. The separation of fine particles is improved. The retardation of the particles may take place in a T-shaped branch pipe, which has one branch connected to the cyclone, a second branch connected to a conveying pipe and a third branch which is formed as a blind space.

IPC 1-7

B04C 5/00; **B04C 9/00**; **F23J 3/04**

IPC 8 full level

B04C 5/02 (2006.01); **B04C 5/00** (2006.01); **B04C 5/04** (2006.01); **B04C 9/00** (2006.01); **F23J 3/04** (2006.01)

CPC (source: EP US)

B04C 5/00 (2013.01 - EP US); **B04C 9/00** (2013.01 - EP US)

Cited by

US5669948A; US5879422A; WO9312889A1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL

DOCDB simple family (publication)

EP 0141073 A2 19850515; **EP 0141073 A3 19880330**; **EP 0141073 B1 19891129**; AT E48246 T1 19891215; DE 3480591 D1 19900104; JP H0446623 B2 19920730; JP S6061060 A 19850408; SE 437943 B 19850325; SE 8304429 D0 19830816; SE 8304429 L 19850217; US 4606739 A 19860819

DOCDB simple family (application)

EP 84109299 A 19840806; AT 84109299 T 19840806; DE 3480591 T 19840806; JP 16989484 A 19840814; SE 8304429 A 19830816; US 64026184 A 19840813