

Title (en)  
MULTIPHASE THERMAL SWITCH

Publication  
**EP 0141286 B1 19920729 (DE)**

Application  
**EP 84111883 A 19841004**

Priority  
DE 3336305 A 19831006

Abstract (en)  
[origin: EP0141286A2] The switch, which is provided for an electrical load, has a housing with a switching contact. A disc-shaped bimetallic device is supported in a switching chamber in the housing on a fitting which is axially movable for the contact switching. An electrically operable temperature-change part is moreover provided for the bimetallic device, the connecting parts of the temperature changing part being fed out of the housing. The axially movable fitting has three star-shaped radial webs projecting transversely to each of which two switching contacts are allocated together with a contact link in the baseplate of the housing associated therewith. The electrically operable temperature change part is arranged in the switching chamber on a side of the bimetallic device opposite the radial webs of the fitting. <IMAGE>

IPC 1-7  
**H01H 37/54**; **H01H 61/02**

IPC 8 full level  
**H01H 37/54** (2006.01); **H01H 61/02** (2006.01)

CPC (source: EP)  
**H01H 37/54** (2013.01); **H01H 61/02** (2013.01)

Designated contracting state (EPC)  
AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)  
**EP 0141286 A2 19850515**; **EP 0141286 A3 19870826**; **EP 0141286 B1 19920729**; DE 3336305 A1 19850502; DE 3485847 D1 19920903

DOCDB simple family (application)  
**EP 84111883 A 19841004**; DE 3336305 A 19831006; DE 3485847 T 19841004