

Title (en)
Lock mechanism for adjustable seat.

Title (de)
Verriegelungseinrichtung für einen verstellbaren Sitz.

Title (fr)
Mécanisme de verrouillage pour siège ajustable.

Publication
EP 0141309 A2 19850515 (EN)

Application
EP 84112104 A 19841009

Priority
JP 18851383 A 19831011

Abstract (en)
A seat is mounted on right and left slide rails (23,24) slidable on right and left guide rails (21,22) so that the position of the seat is adjustable back and forth. Right and left lock mechanisms (25,45) are mounted on the right and left slide rails, respectively, for locking a relative movement between a right or left pair of the slide and guide rails. A handle bar (26) is connected with the left lock mechanism (25), for example, and extends forwardly so that the left lock mechanism is unlocked with the handle bar. The motion of the handle bar for unlocking the left lock mechanism is transmitted through a release wire (44) and link mechanism (39,42) to the right lock mechanism (45) to unlock the right lock mechanism together. The release wire extends from the handle bar adjacent the left slide rail to the right slide rail near the front of the seat. The link means extends backwardly along the right slide rail from the end of the release wire to the right lock mechanism. The link means makes it possible to displace the position of the right end of the release wire toward the front of the seat.

IPC 1-7
B60N 1/08

IPC 8 full level
B60N 2/06 (2006.01); **B60N 2/07** (2006.01); **B60N 2/08** (2006.01)

CPC (source: EP US)
B60N 2/0705 (2013.01 - EP US); **B60N 2/0707** (2013.01 - EP US); **B60N 2/0715** (2013.01 - EP US); **B60N 2/072** (2013.01 - EP US); **B60N 2/0747** (2013.01 - EP US); **B60N 2/0825** (2013.01 - EP US); **B60N 2/0843** (2013.01 - EP US); **B60N 2/0856** (2013.01 - EP US); **B60N 2/0887** (2013.01 - EP US)

Cited by
FR2597041A1; GB2223792A; DE4221111A1; GB2221245A; US4949932A; GB2221245B

Designated contracting state (EPC)
DE FR GB

DOCDB simple family (publication)
US 4635890 A 19870113; DE 3478217 D1 19890622; EP 0141309 A2 19850515; EP 0141309 A3 19850724; EP 0141309 B1 19890517; JP S6080935 A 19850508; JP S6258936 B2 19871208

DOCDB simple family (application)
US 65781784 A 19841005; DE 3478217 T 19841009; EP 84112104 A 19841009; JP 18851383 A 19831011