

Title (en)
LIQUID DISPENSING DEVICE TO BE INTRODUCED INTO A FLUSHING TANK

Publication
EP 0141687 A3 19860326 (FR)

Application
EP 84401602 A 19840731

Priority
FR 8314930 A 19830920

Abstract (en)
[origin: EP0141687A2] The device comprises a fixed element (6) housed in the neck (2) of the container (1) and formed of means (8) forming a discharge opening communicating with the outlet opening of the container (1), a sleeve (9) disposed in the neck (2) of the container, a movable element sliding relative to the fixed element (6), the movable element and the fixed element (6) comprising temporary means for dispensing a given volume "V" of liquid occurring between a high position and a low position of the movable element being formed, on the one hand, by two valves which are spaced apart from each other and produced on the movable element, and, on the other hand, by two seats produced on the fixed element (6). Application to the dispensing of liquid in a flushing tank. <IMAGE>

IPC 1-7
E03D 9/03

IPC 8 full level
E03D 9/02 (2006.01); **E03D 9/03** (2006.01)

CPC (source: EP)
E03D 9/037 (2013.01); **E03D 2009/028** (2013.01)

Citation (search report)
• [X] US 3841524 A 19741015 - EASTER A
• [Y] US 4066187 A 19780103 - NIEMAN CHARLES WAYNE, et al
• [X] FR 1278126 A 19611208 - AUFRA LAB
• [AD] US 2967310 A 19610110 - O'HARE HARRY M

Cited by
DE9414178U1; EP0270409A1; GB2298878A; EP0261882A1; GB2195368A

Designated contracting state (EPC)
BE CH DE GB IT LI LU NL SE

DOCDB simple family (publication)
EP 0141687 A2 19850515; EP 0141687 A3 19860326; DK 445284 A 19850321; DK 445284 D0 19840919; ES 536051 A0 19850601; ES 8505756 A1 19850601; FR 2552136 A1 19850322; JP S60156829 A 19850817

DOCDB simple family (application)
EP 84401602 A 19840731; DK 445284 A 19840919; ES 536051 A 19840919; FR 8314930 A 19830920; JP 19585684 A 19840920