

Title (en)
ANCHORING DEVICE FOR DEVICES USED FOR WORKING ON ROOFS

Publication
EP 0141730 B1 19861029 (FR)

Application
EP 84402138 A 19841024

Priority
FR 8317762 A 19831103

Abstract (en)
[origin: EP0141730A2] 1. A device for anchoring a fitting or material to a roof, the said device (1 or 2), which is secured to a rafter (3, 4 or 58) between two of the elements (5 and 6, 7 and 8) supporting the covering elements, comprising a means (9, 10 or 56) for securing to the rafter and, connected to the said securing means, a member (11, 12, 55) for anchoring the fitting or material, the said device being characterised in that the anchoring member (11, 12, 55) is connected to the securing means (9, 10, 56) by means of a coupling system (13, 14, 54) of any known type which renders the said anchoring member and the said securing means inseparable, whilst allowing for a degree of movement which is sufficient to allow the anchoring member to adopt two positions, one in which the said anchoring member is extended so as to partially project above the roof, called the operative position, and another position in which it is retracted so as to disappear from sight under the covering elements, called the stand-by or inoperative position.

IPC 1-7
E04G 21/32; E04G 3/12; E04G 5/04

IPC 8 full level
E04G 3/26 (2006.01); **E04G 5/04** (2006.01); **E04G 21/32** (2006.01)

CPC (source: EP)
E04G 3/26 (2013.01); **E04G 5/04** (2013.01); **E04G 5/041** (2013.01); **E04G 21/3214** (2013.01)

Cited by
ITFI20120152A1; AT500515A1; FR2755164A1; GB2219826A; GB2219826B; GB2251020A; GB2251020B; FR2588031A1

Designated contracting state (EPC)
AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)
EP 0141730 A2 19850515; **EP 0141730 A3 19850626**; **EP 0141730 B1 19861029**; AT E23205 T1 19861115; DE 3461111 D1 19861204; FR 2554486 A1 19850510; FR 2554486 B1 19860328

DOCDB simple family (application)
EP 84402138 A 19841024; AT 84402138 T 19841024; DE 3461111 T 19841024; FR 8317762 A 19831103