

Title (en)

DEVICE FOR CONTROLLING AND PIECING THE BROKEN YARN DURING THE DOFFING STEP IN A SPINNING MACHINE

Publication

**EP 0142486 B1 19871028 (FR)**

Application

**EP 84870141 A 19841004**

Priority

BE 211650 A 19831005

Abstract (en)

[origin: US4617791A] In spinning machine comprising an underwinding device for winding the last turns, means are provided whereby the last yarn turns are cut positively on the intervention of the underwinding device and means are provided whereby the yarn end originating from the traveller is positively retained by the device to allow starting of the next winding operation at reduced speed, and this end is then released as soon as the spindle assumes its normal operating speed.

IPC 1-7

**D01H 9/16**

IPC 8 full level

**D01H 1/38** (2006.01)

CPC (source: EP US)

**D01H 1/38** (2013.01 - EP US)

Cited by

EP0775769A1; EP0587526A1; EP0462467A1; EP0949366A3; WO9950488A1; KR101256503B1

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

**EP 0142486 A1 19850522; EP 0142486 B1 19871028;** BE 897919 A 19840130; DE 3339670 A1 19850418; DE 3467007 D1 19871203; US 4617791 A 19861021

DOCDB simple family (application)

**EP 84870141 A 19841004;** BE 211650 A 19831005; DE 3339670 A 19831102; DE 3467007 T 19841004; US 65762984 A 19841004