

Title (en)

APPARATUS FOR LOCKING A CLOSURE

Publication

EP 0144221 B1 19900808 (EN)

Application

EP 84308315 A 19841130

Priority

GB 8332392 A 19831205

Abstract (en)

[origin: EP0144221A2] Keepers 1 and 10 are mounted near a jamb of the door, in which jamb the leading edge of the door carrying handle/espagnolette gear is received to lock the door. Using the apparatus embodying the invention, the door can be locked in any one of three additional positions. This provides for the door to be locked open in different ventilating positions without having a sufficient gap between the leading edge of the door and the jamb to permit unauthorised entry. The door is merely slid to the required position and then the espagnolette rods are moved to engage in a desired one of the facing pairs 2, 11, depending on the ventilation gap required.

IPC 1-7

E05B 15/02; E05C 9/04

IPC 8 full level

E05B 15/02 (2006.01); **E05B 65/08** (2006.01); **E05C 9/04** (2006.01); **E05C 17/60** (2006.01)

CPC (source: EP)

E05B 65/087 (2013.01); **E05C 9/041** (2013.01); **E05C 17/60** (2013.01)

Cited by

FR2785935A1; FR2706935A1; GR1001270B; FR2824354A1; EP1270857A1; FR2826684A1; EP0694662A1; GR920100386A; WO2024079545A1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0144221 A2 19850612; EP 0144221 A3 19860611; EP 0144221 B1 19900808; AT E55446 T1 19900815; DE 3482941 D1 19900913; GB 2150633 A 19850703; GB 2150633 B 19870520; GB 8332392 D0 19840111; GB 8430355 D0 19850109; IE 56333 B1 19910619; IE 843087 L 19850605

DOCDB simple family (application)

EP 84308315 A 19841130; AT 84308315 T 19841130; DE 3482941 T 19841130; GB 8332392 A 19831205; GB 8430355 A 19841130; IE 308784 A 19841203