

Title (en)

Method of crimping a heat exchanger end plate onto a header box.

Title (de)

Verfahren zum Einfassen eines Wasserbehälters einer Sammelplatte eines Wärmetauschers.

Title (fr)

Procédé pour le sertissage d'une plaque collectrice d'un échangeur de chaleur sur une boîte à eau.

Publication

EP 0145574 A2 19850619 (FR)

Application

EP 84402394 A 19841123

Priority

FR 8319757 A 19831209

Abstract (en)

[origin: ES8603646A1] The rising edge (9) of the collector plate (5) is stiffened and extends in the assembled state above the rim (4) of the water box (1). The stiffened edge is partially turned over the water box rim. - A line of least resistance (11) is made in the collector plate peripheral edge by a series of aligned holes (10). The collector plate top, above the line of least resistance, is stiffened by forming undulations in it that project outwards and define between them vertically extending segments (13).

[origin: ES8603646A1] The rising edge (9) of the collector plate (5) is stiffened and extends in the assembled state above the rim (4) of the water box (1). The stiffened edge is partially turned over the water box rim. - A line of least resistance (11) is made in the collector plate peripheral edge by a series of aligned holes (10). The collector plate top, above the line of least resistance, is stiffened by forming undulations in it that project outwards and define between them vertically extending segments (13).

Abstract (fr)

Echangeur de chaleur à tubes (6) et dissipateurs (7) dont les tubes débouchent dans une plaque collectrice (5) recouverte par une boîte à eau (1) sertie par un bord montant (9), caractérisé en ce que le bord montant (9) présente sur son pourtour une ligne de moindre résistance (11), en ce que des moyens de raidissement (12, 13) sont prévus dans le bord montant (9) au-dessus de la ligne de moindre résistance (11) et en ce que lesdits moyens de raidissement (12, 13) sont au moins rabattus partiellement sur un rebord périphérique (4) de la boîte à eau dans une position pour laquelle un talon (3) de cette boîte à eau comprime un joint d'étanchéité.

IPC 1-7

F28F 9/02; **F28D 1/04**; **B21D 53/08**

IPC 8 full level

F28F 9/02 (2006.01)

CPC (source: EP US)

F28F 9/0226 (2013.01 - EP US); **F28F 2275/122** (2013.01 - EP US); **Y10S 165/474** (2013.01 - EP US); **Y10T 29/49373** (2015.01 - EP US); **Y10T 29/49892** (2015.01 - EP US); **Y10T 29/49915** (2015.01 - EP US); **Y10T 29/5188** (2015.01 - EP US); **Y10T 403/49** (2015.01 - EP US); **Y10T 403/4983** (2015.01 - EP US)

Cited by

DE3732964A1; US4881595A; US5944095A; EP0838652A3

Designated contracting state (EPC)

BE DE GB IT

DOCDB simple family (publication)

EP 0145574 A2 19850619; **EP 0145574 A3 19850724**; **EP 0145574 B1 19870930**; BR 8406274 A 19851001; CA 1236087 A 19880503; DE 145574 T1 19851107; DE 3466592 D1 19871105; ES 538332 A0 19860101; ES 8603646 A1 19860101; FR 2556461 A1 19850614; FR 2556461 B1 19880826; US 4649628 A 19870317

DOCDB simple family (application)

EP 84402394 A 19841123; BR 8406274 A 19841207; CA 469604 A 19841207; DE 3466592 T 19841123; DE 84402394 T 19841123; ES 538332 A 19841206; FR 8319757 A 19831209; US 67587284 A 19841128