

Title (en)

LUBRICANT FOR METAL FORMING AND PROCESS FOR METAL FORMING

Publication

EP 0146140 A3 19860917 (EN)

Application

EP 84115695 A 19841218

Priority

JP 23782883 A 19831219

Abstract (en)

[origin: EP0146140A2] A substantially water-free, liquid lubricant for metal forming, which comprises (a) a lubricating oil, and (b) at least one phosphoric acid monoester from the group represented by the general formula: RO-@-(OH)₂ wherein R is alkyl, alkylalkenyl or aryl, and optionally (c) at least one member of the group including fatty acids, fatty acid amides and metal soaps, can form a lubricating film with a good heat resistance and good lubricating properties by virtue of the heat generated by deformation and friction during the forming only by wetting the surface of a metallic workpiece (2) or a die (5) with the liquid lubricant, and can work effectively for prevention of galling. Parts or articles with a higher reduction of area and complicated shape can be readily formed. Furthermore, a film having a lubricating effect equivalent to that of the conventional phosphate coating film can be simply obtained with a great contribution to product cost reduction.

IPC 1-7

C10M 137/04; C10M 141/10; B21C 23/32

IPC 8 full level

C10M 137/04 (2006.01); **C10M 141/10** (2006.01); **C10N 30/06** (2006.01); **C10N 40/24** (2006.01); **C10N 50/02** (2006.01); **C10N 80/00** (2006.01)

CPC (source: EP KR)

C10M 129/28 (2013.01 - EP); **C10M 133/16** (2013.01 - EP); **C10M 137/04** (2013.01 - EP KR); **C10M 141/10** (2013.01 - EP);
C10M 2207/12 (2013.01 - EP); **C10M 2207/121** (2013.01 - EP); **C10M 2207/122** (2013.01 - EP); **C10M 2207/125** (2013.01 - EP);
C10M 2207/129 (2013.01 - EP); **C10M 2207/16** (2013.01 - EP); **C10M 2215/08** (2013.01 - EP); **C10M 2215/082** (2013.01 - EP);
C10M 2215/086 (2013.01 - EP); **C10M 2215/12** (2013.01 - EP); **C10M 2215/122** (2013.01 - EP); **C10M 2215/28** (2013.01 - EP);
C10M 2223/04 (2013.01 - EP); **C10M 2223/041** (2013.01 - EP); **C10M 2223/042** (2013.01 - EP); **C10N 2010/00** (2013.01 - EP);
C10N 2010/02 (2013.01 - EP); **C10N 2040/24** (2013.01 - EP); **C10N 2040/241** (2020.05 - EP); **C10N 2040/242** (2020.05 - EP);
C10N 2040/243 (2020.05 - EP); **C10N 2040/244** (2020.05 - EP); **C10N 2040/245** (2020.05 - EP); **C10N 2040/246** (2020.05 - EP);
C10N 2040/247 (2020.05 - EP)

Citation (search report)

- [X] GB 965445 A 19640729 - SHELL INT RESEARCH
- [X] FR 2289601 A1 19760528 - EXXON RESEARCH ENGINEERING CO [US]
- [X] US 2391631 A 19451225 - KINGERLEY JR RICHARD W
- [X] US 2285853 A 19420609 - BAXTER DOWNING FREDERICK, et al
- [X] DE 2145296 A1 19720323
- [E] EP 0158306 A2 19851016 - HOECHST AG [DE]
- [AE] EP 0135932 A2 19850403 - HITACHI LTD [JP]

Cited by

KR100763490B1; EP0227012A1; EP1386982A4; US6103675A; EP2311928A3; EP1176165A1; US7727942B2; US6642292B2;
WO2004050808A3; EP3581635A1; US11453600B2

Designated contracting state (EPC)

CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

EP 0146140 A2 19850626; EP 0146140 A3 19860917; EP 0146140 B1 19910403; DE 3484387 D1 19910508; JP H0439518 B2 19920629;
JP S60130693 A 19850712; KR 850004262 A 19850711; KR 880000067 B1 19880222

DOCDB simple family (application)

EP 84115695 A 19841218; DE 3484387 T 19841218; JP 23782883 A 19831219; KR 840007970 A 19841214