

Title (en)
COMMINUTER FOR TURNINGS

Publication
EP 0146820 B1 19870304 (DE)

Application
EP 84114517 A 19841130

Priority
DE 8335662 U 19831213

Abstract (en)
1. A comminuting device for metal turnings with a driven rotor (2) located in the housing (1) of the comminuting device, on which rotor at the outlet side at least one precomminuting arm (3) is placed, whose precomminuting knife (4) cooperates with comminuting bars (5) arranged on the housing and on which rotor (2) on the outlet side a number of peripherally spaced rotor knives (6) of a fine comminuting section are located, the comminuting edges of which cooperate with the comminuting edges of a number of peripherally spaced stator knives (7) in the comminuting device housing, characterized in that at least one stator knife (7') in the housing (1) of the comminuting device is guided for radial motion from an operational position into an open position uncovering an outlet (10') for coarse lumps.

IPC 1-7
B02C 13/18

IPC 8 full level
B02C 13/18 (2006.01); **B02C 13/28** (2006.01); **B02C 13/286** (2006.01); **B02C 18/06** (2006.01); **B02C 18/18** (2006.01)

CPC (source: EP US)
B02C 18/06 (2013.01 - EP US); **B02C 18/18** (2013.01 - EP US)

Cited by
EP0738560A1; US5785261A; US5224656A; DE4239342A1; US5769337A; US5631356A

Designated contracting state (EPC)
DE FR GB IT

DOCDB simple family (publication)
EP 0146820 A1 19850703; **EP 0146820 B1 19870304**; DE 3462437 D1 19870409; DE 8335662 U1 19840308; JP S60209264 A 19851021; US 4903904 A 19900227

DOCDB simple family (application)
EP 84114517 A 19841130; DE 3462437 T 19841130; DE 8335662 U 19831213; JP 26098884 A 19841212; US 35213089 A 19890515