

Title (en)

CORNER FORMING METHOD FOR SPACER FRAMES OF EDGE-SEALED INSULATING GLAZING UNITS

Publication

**EP 0146883 B1 19870325 (DE)**

Application

**EP 84115287 A 19841212**

Priority

DE 3346671 A 19831223

Abstract (en)

[origin: US4660271A] In a process of manufacturing a spacer frame for a perimeter-bonded insulating glass pane, a metal tubular bar is filled with a granular desiccant and is subsequently bent in each corner-forming portion about an axis which is at right angles to two parallel cheeks of the bar. The two cheeks are drilled through in each of said corner-forming portions to form two bores and a small quantity of the granular desiccant is removed from each of said corner-forming portions through at least one of said bores therein before said corner-forming portion is bent.

IPC 1-7

**E06B 3/66**

IPC 8 full level

**C03C 27/12** (2006.01); **E06B 3/66** (2006.01); **E06B 3/667** (2006.01); **E06B 3/673** (2006.01)

CPC (source: EP US)

**E06B 3/667** (2013.01 - EP US); **E06B 3/67313** (2013.01 - EP US); **Y10T 29/49929** (2015.01 - EP US); **Y10T 29/49986** (2015.01 - EP US)

Cited by

EP0435077A3; EP0318749A1; DE4231683A1

Designated contracting state (EPC)

AT CH DE FR IT LI

DOCDB simple family (publication)

**EP 0146883 A2 19850703**; **EP 0146883 A3 19850807**; **EP 0146883 B1 19870325**; AT E26150 T1 19870415; DE 3346671 C1 19850704;  
DE 3462816 D1 19870430; US 4660271 A 19870428

DOCDB simple family (application)

**EP 84115287 A 19841212**; AT 84115287 T 19841212; DE 3346671 A 19831223; DE 3462816 T 19841212; US 68290484 A 19841218