

Title (en)

BROADBAND POLARISATION FILTER

Publication

EP 0147693 A3 19880316 (DE)

Application

EP 84114869 A 19841206

Priority

DE 3345689 A 19831216

Abstract (en)

[origin: EP0147693A2] This broadband polarisation filter is used for the separation of orthogonal, linear-polarised electromagnetic waves. A waveguide section 4, on the input side, of rectangular or square cross-section, has two coupling windows 11, located on opposite sides from each other. Rectangular waveguide arms 2, 3 branch out from these coupling windows 11 and open into a common broadband fork 8 after passing through curves 5, 7. In order to provide a particularly compact spatial design, the lateral waveguide arms 2, 3 are allowed to diverge at an acute angle alpha , and, after being guided parallel to one another and then passing through an S-shaped E-plane curve 7 in the broadband fork 8, are led together and the waveguide arm 9, flowing out of the input-side waveguide section 4 is displaced in parallel before the broadband fork 8, by means of an S-shaped E-plane curve 10, with respect to the major direction and the plane of the lateral waveguide sections 2, 3.

IPC 1-7

H01P 1/161

IPC 8 full level

H01P 1/161 (2006.01)

CPC (source: EP)

H01P 1/161 (2013.01)

Citation (search report)

- [YD] FR 2371065 A1 19780609 - LICENTIA GMBH [DE]
- [Y] US 4176330 A 19791127 - DITULLIO JOSEPH G [US], et al
- [A] DE 2521956 A1 19761118 - SIEMENS AG
- [A] FR 2518822 A1 19830624 - VITALINK COMMUNICATIONS CORP [US]
- [A] US 3325751 A 19670613 - PHILLIPS ROBERT M
- [A] US 3201717 A 19650817 - MARCEL GROSBOIS, et al

Cited by

EP0419892A3; EP0196065A1; US4700154A

Designated contracting state (EPC)

FR GB IT SE

DOCDB simple family (publication)

EP 0147693 A2 19850710; EP 0147693 A3 19880316; EP 0147693 B1 19920513; DE 3345689 A1 19850711; DE 3345689 C2 19920409

DOCDB simple family (application)

EP 84114869 A 19841206; DE 3345689 A 19831216