

Title (en)
LUBRICANT

Publication
EP 0148232 B1 19881026 (DE)

Application
EP 84902586 A 19840703

Priority
DE 3324475 A 19830707

Abstract (en)
[origin: DE3324475A1] To provide a lubricant which may be removed by washing with the water, a water-soluble carrier is used which is preferably comprised of polyethylene glycol (500), wherein is introduced at least one lubricant preferably in the form of a wax and/or a fatty acid and/or a polysiloxane and/or finely dispersed silica, the water-soluble carrier representing approximately from 75 to 95 parts by weight and the lubricant, respectively the lubricants, admixed representing the remainder.

IPC 1-7
A44B 19/00; C08L 71/02; C10M 169/04; F16N 15/00

IPC 8 full level
A44B 19/00 (2006.01); **C08L 71/02** (2006.01); **C10M 111/00** (2006.01); **C10M 169/04** (2006.01); **F16N 15/00** (2006.01); **C10N 30/06** (2006.01); **C10N 40/00** (2006.01); **C10N 40/25** (2006.01)

CPC (source: EP)
C10M 101/02 (2013.01); **C10M 105/12** (2013.01); **C10M 105/32** (2013.01); **C10M 105/68** (2013.01); **C10M 107/04** (2013.01); **C10M 107/34** (2013.01); **C10M 107/50** (2013.01); **C10M 111/00** (2013.01); **C10M 133/16** (2013.01); **C10M 143/04** (2013.01); **C10M 155/02** (2013.01); **C10M 159/06** (2013.01); **C10M 169/04** (2013.01); **C10M 2201/102** (2013.01); **C10M 2205/14** (2013.01); **C10M 2205/16** (2013.01); **C10M 2207/126** (2013.01); **C10M 2207/283** (2013.01); **C10M 2209/104** (2013.01); **C10M 2215/08** (2013.01); **C10M 2229/02** (2013.01); **C10N 2020/06** (2013.01); **C10N 2040/46** (2020.05); **C10N 2050/10** (2013.01)

Designated contracting state (EPC)
AT BE CH DE FR GB LI LU NL SE

DOCDB simple family (publication)
DE 3324475 A1 19850117; DE 3474836 D1 19881201; EP 0148232 A1 19850717; EP 0148232 B1 19881026; JP H0251960 B2 19901109; JP S60501814 A 19851024; WO 8500378 A1 19850131

DOCDB simple family (application)
DE 3324475 A 19830707; DE 3474836 T 19840703; EP 8400202 W 19840703; EP 84902586 A 19840703; JP 50261184 A 19840703