

Title (en)

IMPROVED CONTAINER.

Title (de)

VERBESSERTER BEHÄLTER.

Title (fr)

RECIPIENT AMELIORE.

Publication

EP 0148894 A1 19850724 (EN)

Application

EP 84902575 A 19840629

Priority

AU PG003683 A 19830629

Abstract (en)

[origin: WO8500156A1] A container (10), for dispensing pills, powders etc., comprising a body (11) and a lid (12) formed of a resilient material; said lid (12) is rotatably mounted on the body with its inside surface in juxtaposition with an end of the body; said end being of an annular shape and surrounded on its outer periphery by an outer side wall (15) and on its inner periphery by an inner side wall (14); at least one aperture being formed in the said end; said lid (12) shaped to closely correspond to the said end of the body and formed with at least one aperture which may be moved into and out of register with the aperture(s) on the end of the body (11); said container (10) is characterised in that the inner and outer side walls (14, 15) of the body (11) and the lid (12) are formed with cooperating arcuate inclined surfaces (18, 19) such that the end of the body (11) and the lid (12) are drawn into close juxtaposition by the action of the inclined surfaces.

Abstract (fr)

Récipient (10) servant à la distribution de comprimés, poudres etc., comprenant un corps (11) et un couvercle (12) composé d'un matériau élastique; le couvercle (12) est monté de manière rotative sur le corps, sa surface interne étant juxtaposée à une extrémité du corps; l'extrémité possède une forme annulaire et est entourée sur sa périphérie externe par une paroi latérale externe (15) et sur sa périphérie interne par une paroi latérale interne (14); au moins une ouverture est aménagée dans cette extrémité; le couvercle (12) est façonné de manière à s'adapter étroitement à l'extrémité du corps et présente au moins une ouverture pouvant être alignée ou non avec l'ouverture (ou les ouvertures) sur l'extrémité du corps (11); le récipient (10) se caractérise par le fait que les parois latérales interne et externe (14, 15) du corps (11) et le couvercle (12) présentent des surfaces inclinées arquées agissant de concert (18, 19), de sorte que l'extrémité du corps (11) et le couvercle (12) sont juxtaposés étroitement sous l'effet des surfaces inclinées.

IPC 1-7

B65D 83/04; B65D 83/06

IPC 8 full level

B65D 83/04 (2006.01); **B65D 83/06** (2006.01)

CPC (source: EP)

B65D 83/06 (2013.01)

Designated contracting state (EPC)

AT BE CH DE FR GB LI LU NL SE

DOCDB simple family (publication)

WO 8500156 A1 19850117; AU 2991384 A 19850103; EP 0148894 A1 19850724; EP 0148894 A4 19871123; JP S60501652 A 19851003

DOCDB simple family (application)

AU 8400120 W 19840629; AU 2991384 A 19830629; EP 84902575 A 19840629; JP 50257784 A 19840629