

Title (en)
ANCHORAGES FOR RAIL TRACKS

Publication
EP 0149513 B1 19891220 (EN)

Application
EP 85300061 A 19850104

Priority
GB 8400956 A 19840113

Abstract (en)
[origin: EP0149513A2] An adjustable rail anchorage assembly comprises a base sole plate with a laterally adjustable abutment member (11) to locate the bottom flange of the rail, an adjusting cam (12) having a circular bearing surface (45) to engage the abutment member and an eccentric connection with the sole plate. In the embodiment of Figures 1 to 7 there is a foot (10) welded to the sole plate and having an upstanding spigot (20) engaging in a socket (46) in the cam. A bolt (13) can be introduced through a slot (22) and has a nut (14) acting as a clamp on the cam. In the embodiment of Figures 8 to 11 the foot (50) has a socket (51) and the cam has a boss (52) fitting in the socket. In the embodiment of Figures 12 to 15 the abutment member has four spaced feet (61) which hold the shoulder (69) clear above the bottom flange (64) and permit small vertical movements of the rail.

IPC 1-7
B66C 7/08; **E01B 9/32**

IPC 8 full level
B66C 7/08 (2006.01); **E01B 9/32** (2006.01)

CPC (source: EP)
E01B 9/32 (2013.01)

Cited by
US5344072A; EP0233032A3; CN113187813A; EP0855465A3; CN113374789A; GB2551404A; CN108100866A; CN109311638A; GB2551404B; US11180893B2; EP2133467A1; DE102008028092A1; US8757510B2

Designated contracting state (EPC)
AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)
EP 0149513 A2 19850724; **EP 0149513 A3 19850807**; **EP 0149513 B1 19891220**; AT E48862 T1 19900115; AU 3760885 A 19850718; AU 583024 B2 19890420; DE 3574888 D1 19900125; GB 8400956 D0 19840215; ZA 85264 B 19850925

DOCDB simple family (application)
EP 85300061 A 19850104; AT 85300061 T 19850104; AU 3760885 A 19850111; DE 3574888 T 19850104; GB 8400956 A 19840113; ZA 85264 A 19850111