

Title (en)
ELECTRIC CIRCUIT ELEMENT

Publication
EP 0150486 A3 19860430 (DE)

Application
EP 84116213 A 19841222

Priority
• DE 3402371 A 19840125
• DE 3402372 A 19840125

Abstract (en)
[origin: US4594489A] The load-isolating switch comprises two coaxial electrodes 1 and 2, which are mechanically connected by an interposed insulator 3. A cam 4 is provided on the insulator 3 and is spanned by at least one contact bridge 5, which is axially displaceable by an axially displaceable slider 10, which has coupling elements 13, 14 for engaging the or each contact bridge 5. In one position the or each contact bridge 5 is in contact with both electrodes 1 and 2. The or each contact bridge is adapted to slide up on an inclined surface 4a of the cam to disengage the contact bridge 5 from one of said electrodes and is movable to a second position in which said slider is disengaged from at least said one electrode.

IPC 1-7
H01H 1/12; **H01H 31/32**

IPC 8 full level
H01H 1/12 (2006.01); **H01H 1/36** (2006.01); **H01H 31/32** (2006.01); **H01H 1/021** (2006.01); **H01H 1/54** (2006.01); **H01H 15/10** (2006.01); **H01H 33/76** (2006.01)

CPC (source: EP US)
H01H 1/365 (2013.01 - EP US); **H01H 1/021** (2013.01 - EP US); **H01H 1/54** (2013.01 - EP US); **H01H 15/102** (2013.01 - EP US); **H01H 33/765** (2013.01 - EP US)

Citation (search report)
• [A] FR 1541812 A 19681011 - MERLIN GERIN
• [A] DE 1137102 C
• [A] DE 1921160 B2 19720210
• [AD] US 4011426 A 19770308 - LANGE EMIL

Cited by
EP0971383A3; FR2745943A1; EP0391049A1; US5070221A; WO9733292A1

Designated contracting state (EPC)
BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)
EP 0150486 A2 19850807; **EP 0150486 A3 19860430**; **EP 0150486 B1 19880511**; DE 3402372 A1 19850801; DE 3471196 D1 19880616; DE 8609229 U1 19860605; HU 189962 B 19860828; HU T37292 A 19851128; US 4594489 A 19860610

DOCDB simple family (application)
EP 84116213 A 19841222; DE 3402372 A 19840125; DE 3471196 T 19841222; DE 8609229 U 19860405; HU 28085 A 19850124; US 69311985 A 19850122