

Title (en)
CYLINDER LOCK

Publication
EP 0152350 A3 19860716 (FR)

Application
EP 85400201 A 19850207

Priority
• FR 8402312 A 19840215
• FR 8415109 A 19841002

Abstract (en)
[origin: EP0152350A2] The cylinder lock consists of a body having at least one drilled hole in which a rotor and stator are mounted coaxially. The stator (5) is mounted so that it can slide axially in the body (1) and is stopped from rotating by at least one locking pin (6) itself mounted so that it can slide axially between the body (1) and the stator (5). The stator (5) presses continually against the rotor (8), which is itself pressed against a flange (9) fixed on to the body (1) under the action of an elastic component (15). Use in the production of locks. <IMAGE>

IPC 1-7
E05B 27/08

IPC 8 full level
E05B 27/08 (2006.01)

CPC (source: EP)
E05B 27/083 (2013.01)

Citation (search report)
• [A] FR 1537981 A 19680830
• [A] US 2588230 A 19520304 - GEORGE HARRY F

Cited by
DE4230591A1; EP2233667A1; FR2943706A1

Designated contracting state (EPC)
CH DE GB IT LI

DOCDB simple family (publication)
EP 0152350 A2 19850821; EP 0152350 A3 19860716; ES 540382 A0 19860416; ES 8606564 A1 19860416

DOCDB simple family (application)
EP 85400201 A 19850207; ES 540382 A 19850213