

Title (en)
GROUND ATTACHING DEVICE

Publication
EP 0152530 B1 19881130 (DE)

Application
EP 84112151 A 19841010

Priority
CH 74684 A 19840216

Abstract (en)
[origin: EP0152530A1] 1. Ground mounting device for poles (45) projecting away from the ground (31) comprising a base member (11) or anchorage member anchorable in the ground (31), the base member having, at the bottom, a base wall (13) securable relative to the ground (31) by a central anchoring or connection screw (12) and rotatable about a first axis of rotation (33) standing approximately perpendicular to the ground (31), above this a side wall (13) extending around it and, at the top, an access opening (15) surrounded by a circular support surface (18) extending obliquely to the base wall (13) and of such a size that the anchoring screw (12) is introducible and accessible through the access opening (15), and comprising a pole support member (16) which has, at the top, a connection region (21) for the pole (45), beneath this a side wall (20) extending around it and, at the bottom, a mounting wall (23) having a circular support surface (19) complementary to the contact surface (18), wherein, to enable rotation about a second axis of rotation (24) extending perpendicular to the contact or support surface (18, 19, respectively) the mounting wall is provided with a central bore (22) for the through guidance of a threaded bolt (27) which fixedly connects the mounting wall (23) with the base member (11), produces a fixed axially clamped connection between the contact surface (18) and the support surface (19) and stands perpendicular to the contact surface (18) or the support surface (19), with the threaded bolt (27) being clamped against the base wall (23) and being accessible through the entrance opening (36) in the upper region of the pole support member (16), characterised in that a rotationally symmetrical axial plug connection (25, 26) concentric to the second axis of rotation (24) is provided radially outside of the access opening (15) between the base wall (13) and the mounting wall (23); and in that the central threaded bolt (27) is secured to the base member (11) in the region of the circumference of the access opening (15), however still radially within the plug connection (25, 26), through a threaded connection (37, 37', 37'') which is accessible and actuable from above when the pole support member (16) is removed.

IPC 1-7
E02D 27/42; **E04H 12/22**

IPC 8 full level
E02D 27/00 (2006.01); **E02D 27/42** (2006.01); **E04H 12/22** (2006.01); **E04H 17/22** (2006.01); **G11B 7/085** (2006.01)

CPC (source: EP US)
E02D 27/42 (2013.01 - EP US); **E04H 12/2284** (2013.01 - EP US); **G11B 7/08517** (2013.01 - EP US); **Y10T 403/32278** (2015.01 - EP US)

Cited by
DE102008000382A1; DE3531087A1; EP0214519A3; AU586497B2; WO9324357A1

Designated contracting state (EPC)
AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)
EP 0152530 A1 19850828; **EP 0152530 B1 19881130**; CA 1237568 A 19880607; DE 3475416 D1 19890105; IN 161404 B 19871128; JP H0451612 B2 19920819; JP S61501274 A 19860626; KR 850700265 A 19851226; KR 930001426 B1 19930227; ZA 851122 B 19851030

DOCDB simple family (application)
EP 84112151 A 19841010; CA 474459 A 19850215; DE 3475416 T 19841010; IN 80CA1985 A 19850206; JP 50446184 A 19841210; KR 850700241 A 19850928; ZA 851122 A 19850214