

Title (en)

INK JET PRINTER

Publication

EP 0153436 B1 19900404 (DE)

Application

EP 84102986 A 19840319

Priority

CH 93984 A 19840227

Abstract (en)

[origin: US4620195A] A method is proposed for fabricating components of an ink droplet generator for generating a sequence of charged, detected and deflected ink droplets for an ink jet printer, as is proposed an ink droplet generator fabricated thereby. The method which is based upon multi-layer technology involves forming the charging electrodes and the detection electrodes by removing unnecessary metal coating from a support element metallically coated on at least one side of the support element and forming the deflection electrodes by removing unnecessary metal coating from a polyimide foil coated on at least one side thereof. The polyimide foil is mounted on a substrate constructed as a support element. The arrangement defining the ink droplet generator comprises a first module formed from both board or panel-like support elements and a second module formed from both board or panel-like support elements.

IPC 1-7

B41J 2/005

IPC 8 full level

B41J 2/005 (2006.01); **B41J 2/085** (2006.01); **B41J 2/09** (2006.01); **B41J 2/135** (2006.01)

CPC (source: EP US)

B41J 2/02 (2013.01 - EP US); **B41J 2/085** (2013.01 - EP US); **B41J 2/09** (2013.01 - EP US); **B41J 2202/22** (2013.01 - EP US)

Cited by

FR2763870A1; EP0613778A3; US6511164B1; WO9855315A1; WO9828147A1; US6357860B1; US6467880B2

Designated contracting state (EPC)

AT CH DE FR GB LI SE

DOCDB simple family (publication)

EP 0153436 A2 19850904; EP 0153436 A3 19860326; EP 0153436 B1 19900404; AT E51583 T1 19900415; BE 901198 A 19850329; DE 3481833 D1 19900510; US 4620195 A 19861028

DOCDB simple family (application)

EP 84102986 A 19840319; AT 84102986 T 19840319; BE 214102 A 19841204; DE 3481833 T 19840319; US 70052285 A 19850211