

Title (en)

KEY WITH A MOVABLE BIT, CYLINDER AND LOCK THEREFOR

Publication

EP 0154755 B1 19870729 (FR)

Application

EP 84400694 A 19840409

Priority

FR 8403944 A 19840314

Abstract (en)

[origin: ES287340U] A key comprises a key body provided with at least one translatably movable plunger able to be displaced in a housing provided in the key, the plunger being intended to co-operate with a positioning member provided in the recess of a rotor so as to project from its recess and to push a movable pin of the rotor into a position permitting rotation of the barrel rotor relative to the stator. The key comprises in its head a constricted zone, and the recess of the movable plunger is provided in this constricted zone.

IPC 1-7

E05B 35/00; **E05B 27/00**

IPC 8 full level

E05B 19/00 (2006.01); **E05B 19/06** (2006.01); **E05B 27/00** (2006.01); **E05B 27/06** (2006.01); **E05B 35/00** (2006.01)

CPC (source: EP US)

E05B 19/0017 (2013.01 - EP US); **E05B 35/003** (2013.01 - EP US); **E05B 19/0047** (2013.01 - EP US); **Y10T 70/7565** (2015.04 - EP US); **Y10T 70/7819** (2015.04 - EP US); **Y10T 70/7881** (2015.04 - EP US); **Y10T 70/7944** (2015.04 - EP US)

Cited by

FR2776327A1; DE4219052C1; FR2619149A1; EP0359885A1; US5520035A; US5784910A; US5839308A; CZ298594B6; FR2802234A1; FR2802233A1; WO9949161A1

Designated contracting state (EPC)

AT BE CH DE GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0154755 A1 19850918; **EP 0154755 B1 19870729**; AT E28680 T1 19870815; DE 3465124 D1 19870903; ES 287340 U 19860401; ES 287340 Y 19861116; FR 2561294 A1 19850920; FR 2561294 B1 19861003; OA 07964 A 19870131; US 4667495 A 19870526

DOCDB simple family (application)

EP 84400694 A 19840409; AT 84400694 T 19840409; DE 3465124 T 19840409; ES 287340 U 19840425; FR 8403944 A 19840314; OA 58538 A 19850314; US 71122085 A 19850313