

Title (en)

VALVE TIMING GEAR FOR AN INTERNAL-COMBUSTION ENGINE

Publication

EP 0155261 B1 19890614 (DE)

Application

EP 85890059 A 19850312

Priority

AT 84384 A 19840314

Abstract (en)

[origin: US4635592A] In an internal combustion engine with a cylinder (1), the cylinder head (2) has four valves (3, 4) inclined towards each other and arranged to be radially aligned with respect to the combustion chamber, pairs of the valves being operable by a common camshaft (6) by means of conical cams (7). To make it possible to use such a valve control for high rotational speeds, too, bucket type tappets (8) are displaceably mounted between the radially aligned valves (3, 4) and the conical cams (7) in the cylinder head (2).

IPC 1-7

F01L 1/26; F01L 31/22

IPC 8 full level

F01L 1/26 (2006.01); **F01L 13/00** (2006.01); **F01L 31/22** (2006.01); **F02B 1/04** (2006.01); **F02F 1/24** (2006.01); **F02F 1/42** (2006.01)

CPC (source: EP US)

F01L 1/205 (2013.01 - EP US); **F01L 1/24** (2013.01 - EP US); **F01L 1/262** (2013.01 - EP US); **F01L 13/0042** (2013.01 - EP US);
F01L 1/0532 (2013.01 - EP US); **F01L 1/08** (2013.01 - EP US); **F01L 2003/256** (2013.01 - EP US); **F02B 1/04** (2013.01 - EP US);
F02B 2275/18 (2013.01 - EP US); **F02F 1/4214** (2013.01 - EP US); **F02F 2001/246** (2013.01 - EP US)

Cited by

EP0235121A1; DE3818636A1; AT400971B; DE3838305A1; FR2668797A1; EP0197914A1; WO9905404A1; WO2009056237A1

Designated contracting state (EPC)

AT DE FR GB IT

DOCDB simple family (publication)

EP 0155261 A2 19850918; EP 0155261 A3 19870107; EP 0155261 B1 19890614; EP 0155261 B2 19960320; AT 382933 B 19870427;
AT A84384 A 19860915; AT E44074 T1 19890615; DE 3571061 D1 19890720; US 4635592 A 19870113

DOCDB simple family (application)

EP 85890059 A 19850312; AT 84384 A 19840314; AT 85890059 T 19850312; DE 3571061 T 19850312; US 70976185 A 19850307