

Title (en)

HIGH-VOLTAGE HIGH-POWER FUSE

Publication

EP 0155373 B1 19891011 (DE)

Application

EP 84114942 A 19841207

Priority

DE 3409957 A 19840317

Abstract (en)

[origin: US4617544A] An HRC-fuse as an insulating body surrounding a main fusible conductor and an auxiliary fusible conductor connected to a spring biased impact pin. A conductive cap serving as a terminal for the fusible conductors is arranged on the insulating body and is provided with an outlet opening opposite the impact pin. A tripping hollow pin or sleeve coaxially surrounds at least a part of the impact pin and passes through the outlet opening. A bimetal release pawl is arranged in the one cap parallel to the pin and being electrically connected to the fusible conductors. The pawl engages a rest on the tripping sleeve to counteract a biasing spring. The impact pin and the tripping sleeve are triggered independently one from the other either by a short-circuit current melting the auxiliary conductor, or by an overload which heats up the bimetal release and triggers the sleeve. Both the tripping sleeve and the impact pin act on a load interruptor arranged opposite the outlet opening.

IPC 1-7

H01H 71/14; H01H 85/30

IPC 8 full level

H01H 85/36 (2006.01); **H01H 37/76** (2006.01); **H01H 71/14** (2006.01); **H01H 85/02** (2006.01); **H01H 85/042** (2006.01); **H01H 85/12** (2006.01);
H01H 85/30 (2006.01); **H01H 89/00** (2006.01)

CPC (source: EP US)

H01H 71/14 (2013.01 - EP US); **H01H 85/306** (2013.01 - EP US); **H01H 2085/0258** (2013.01 - EP US)

Cited by

EP0881654A1; FR2764108A1; WO2010105648A1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

EP 0155373 A2 19850925; EP 0155373 A3 19870422; EP 0155373 B1 19891011; AT E47250 T1 19891015; DE 3409957 A1 19850919;
DE 3409957 C2 19890209; DE 3480142 D1 19891116; JP S60211735 A 19851024; JP S6153813 B2 19861119; US 4617544 A 19861014

DOCDB simple family (application)

EP 84114942 A 19841207; AT 84114942 T 19841207; DE 3409957 A 19840317; DE 3480142 T 19841207; JP 5069585 A 19850315;
US 71327385 A 19850318