

Title (en)  
CONTACT ARRANGEMENT FOR A VACUUM SWITCH

Publication  
**EP 0155376 B1 19870603 (DE)**

Application  
**EP 84115139 A 19841211**

Priority  
DE 3407088 A 19840227

Abstract (en)  
[origin: US4620074A] A contact arrangement comprising two cup-type contacts having hollow-cylindrical contact carriers arranged coaxially with each other and having slots inclined in the same sense to the longitudinal axis of the contact arrangement. The slots act as a coil for generating a magnetic field for minimizing arc currents. The condition  $\frac{D}{s} > 1$  is met in a range of the outside diameter D of the contact carriers of from 60 to 150 mm, a predetermined height HT of the contact carriers, a number s of the slots and an azimuth B of the slots. With this design, a contact arrangement with an axial magnetic field of at least 3.5 uT/A is obtained.

IPC 1-7  
**H01H 33/66**

IPC 8 full level  
**H01H 33/66** (2006.01); **H01H 33/664** (2006.01)

CPC (source: EP US)  
**H01H 33/6642** (2013.01 - EP US)

Cited by  
CN112420444A; DE3724811A1; DE19651745C1; US5064976A; DE3724813A1; US5313030A; CN108028150A; DE102004031887B3; EP0747917A3; EP2261940A1; FR2946792A1; DE10029763A1; DE10030670A1; DE10030670C2; RU203212U1; DE10029763B4; DE102012221844A1; US6307308B1; US8168910B2; US8164019B2; WO9826441A1; WO2014094724A1; US6891122B2; US6720515B2; US8288674B2; WO0197242A1; WO0199132A1; DE102015217647A1; WO2017045862A1; US10418211B2

Designated contracting state (EPC)  
CH DE FR GB LI

DOCDB simple family (publication)  
**EP 0155376 A1 19850925; EP 0155376 B1 19870603**; DE 3407088 A1 19850829; DE 3464103 D1 19870709; JP H0359531 B2 19910910; JP S60205925 A 19851017; US 4620074 A 19861028

DOCDB simple family (application)  
**EP 84115139 A 19841211**; DE 3407088 A 19840227; DE 3464103 T 19841211; JP 3624585 A 19850225; US 70442885 A 19850222