

Title (en)

Method for preparing hydrocarbon catalytic cracking catalyst compositions.

Title (de)

Methode zur Herstellung von Katalysatorzusammensetzungen für das katalytische Kracken von Kohlenwasserstoffen.

Title (fr)

Méthode de préparation de compositions catalytiques pour le craquage catalytique d'hydrocarbures.

Publication

EP 0155824 A2 19850925 (EN)

Application

EP 85301785 A 19850314

Priority

JP 4996884 A 19840315

Abstract (en)

A catalyst composition suitable for catalytic cracking of a heavy hydrocarbon oil containing large amounts of metal contaminants is prepared by the steps of spray-drying an aqueous slurry containing a flash calcined alumina obtained by contacting an aluminum hydroxide prepared Bayer's process with a hot air of 350-700 °C for 5 seconds or less, clay being predominantly composed of silica and alumina, a precursor of a siliceous inorganic oxide and a crystalline aluminosilicate; washing this particle until the alkali metal content therein is reduced to 1.0wt% or less as oxide; and thereafter incorporating a rare earth component in the particle.

IPC 1-7

B01J 37/02; B01J 35/08; B01J 29/06; B01J 23/10

IPC 8 full level

C10G 11/02 (2006.01); **B01J 29/06** (2006.01); **B01J 29/08** (2006.01); **B01J 37/00** (2006.01); **C10G 11/00** (2006.01); **C10G 11/05** (2006.01)

CPC (source: EP US)

B01J 29/084 (2013.01 - EP US); **B01J 29/088** (2013.01 - EP US); **B01J 37/0045** (2013.01 - EP US); **C10G 11/05** (2013.01 - EP US);
B01J 2229/42 (2013.01 - EP US)

Cited by

US4880787A; FR2764213A1; EP0903177A1; US6043187A; EP0377586A4; EP0256875A3; US6203695B1; EP2342410A2

Designated contracting state (EPC)

DE FR GB NL

DOCDB simple family (publication)

EP 0155824 A2 19850925; EP 0155824 A3 19870909; EP 0155824 B1 19910403; DE 3582348 D1 19910508; JP H0459014 B2 19920921;
JP S60193543 A 19851002; US 4631261 A 19861223

DOCDB simple family (application)

EP 85301785 A 19850314; DE 3582348 T 19850314; JP 4996884 A 19840315; US 71307585 A 19850315