

Title (en)

Locking device for a switch point.

Title (de)

Vorrichtung zum Verriegeln einer Weichenzunge.

Title (fr)

Dispositif pour le verrouillage d'une lame d'aiguillage.

Publication

EP 0156351 A2 19851002 (DE)

Application

EP 85103526 A 19850326

Priority

DE 3411142 A 19840326

Abstract (en)

1. Locking device for a switch point (12) having a stock rail (10), in which a locking element (16), which can be pivoted about a first axis (B) and effects locking, extends from the switch point or from a tongue attachment, and along a second axis (C) is in turn hinged on to a swivel element (18) which can be pivoted about a third axis (A) by means of a switch or sliding element (26), characterised in that the third axis (A) is arranged on the stock rail (10) or at a defined non-variable distance from the stock rail (10), that when the swivel element (18) is pivoted the locking element (16) passes a zero position (32) defined by a plane extending at right angles to the stock rail (10), and containing the first, second and third axes (B, C, A), and that when the swivel element is pivoted further and thus the locking element passes the zero position, the swivel element is pivoted into a first end position in such a way that the switch point (12) lies permanently on the stock rail (10), thus effecting locking, and that when the swivel element has been pivoted into the first end position, the first and second axes (B, C) are arranged in such a way with respect to the third axis (A) that a force from the switch point acts upon the locking element, thus preventing the release of said switch point.

Abstract (de)

Eine Vorrichtung zum Verriegeln von Weichen zeichnet sich dadurch aus, daß die Weichenzunge (12) mittels eines Verschlussehebels (16) an einer Backenschiene (10) festlegbar ist, der mittels eines Drehelementes (18) in eine Verriegelungsstellung verschwenkbar ist, die durch Krafteinwirkung auf die Weichenzunge (12) nicht aufhebbar ist. In die Verriegelungsstellung sind die Backenschiene (10) und die Weichenzunge fest verklammert und bilden somit eine Einheit, die auch dann nicht aufgehoben wird, wenn z.B. eine Lageveränderung der Backenschiene (10) erfolgen sollte.

IPC 1-7

E01B 7/02; E01B 7/20

IPC 8 full level

E01B 7/02 (2006.01); **E01B 7/20** (2006.01)

CPC (source: EP)

B61L 5/10 (2013.01); **E01B 2202/08** (2013.01)

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

EP 0156351 A2 19851002; **EP 0156351 A3 19870527**; **EP 0156351 B1 19891018**; AT E47439 T1 19891115; DE 3411142 A1 19851003; DE 3573814 D1 19891123

DOCDB simple family (application)

EP 85103526 A 19850326; AT 85103526 T 19850326; DE 3411142 A 19840326; DE 3573814 T 19850326