

Title (en)

ELECTRON-IMPACT TYPE OF ION SOURCE

Publication

EP 0156473 B1 19900328 (EN)

Application

EP 85300853 A 19850208

Priority

JP 5803084 A 19840326

Abstract (en)

[origin: US4620102A] A double grid anode is characterized in that said anode is comprised of a first cage-like anode made of a metal grid or wire gauze that permits that passage of electrons and that has an open end, a second anode which also consists of a metal grid or wire gauze located at the open end side of said first anode, a hot-cathode filament arranged around the outer periphery of said first anode, and an ion-extraction electrode which faces said anode.

IPC 1-7

H01J 27/08

IPC 8 full level

G01N 27/62 (2006.01); **H01J 27/08** (2006.01); **H01J 27/20** (2006.01); **H01J 37/08** (2006.01); **H01J 49/10** (2006.01); **H01J 49/14** (2006.01)

CPC (source: EP US)

H01J 27/205 (2013.01 - EP US); **H01J 49/147** (2013.01 - EP US)

Cited by

GB2189645A; GB2189645B; EP0624898A3; USRE35701E; CN1037133C

Designated contracting state (EPC)

DE FR GB

DOCDB simple family (publication)

US 4620102 A 19861028; DE 3576880 D1 19900503; EP 0156473 A2 19851002; EP 0156473 A3 19870429; EP 0156473 B1 19900328;
JP H0234410 B2 19900803; JP S60202649 A 19851014

DOCDB simple family (application)

US 71549885 A 19850325; DE 3576880 T 19850208; EP 85300853 A 19850208; JP 5803084 A 19840326