

Title (en)

Device for the pivotable fixing of a lid and/or a toilet seat on a toilet bowl.

Title (de)

Vorrichtung zur schwenkbaren Befestigung eines Klosett-Deckels und/oder -Sitzes an einem Klosettbecken.

Title (fr)

Dispositif pour la fixation d'un couvercle de WC et/ou d'un siège sur une cuvette de WC de manière pivotante.

Publication

EP 0156967 A1 19851009 (DE)

Application

EP 84114232 A 19841124

Priority

DE 3405350 A 19840215

Abstract (en)

1. A device for the pivotable attachment of a toilet lid and/or seat on a lavatory pan, the lid and/or seat being mounted by means of horizontal pivot bolts (1, 1') and fixing parts adapted to be secured by means of two screws (9, 9') which engage cut-outs in the lavatory pan, the pivot bolts engaging bearing lugs of the cover and/or seat being removably secured to the fixing parts by means of a locking device, there being constructed on the pivot bolts (1, 1') integral projections (2, 2') which are mounted to engage corresponding longitudinal recesses (15, 15') of the fixing parts, characterised in that the locking device comprises a one-piece locking bolt (12, 12') mounted on the fixing part (4, 4') in such a way that it can be pivoted or pushed into a locking bolt recess (annular groove 3') in the projection (2, 2') on the fixing part (4, 4'), the axis of the longitudinal recess (15, 15') in the fixing part (4') extending in an offset relationship to the axis of the fixing part (4), the projections (2, 2') of the pivot mounting bolts (1') being mounted to rotate in relation to the fixing parts (4') and in the longitudinal recess (15, 15').

Abstract (de)

Bei einer Vorrichtung zu schwenkbaren Befestigung eines Klosett-Deckels und/oder -Sitzes an einem Klosettbecken, wobei der Deckel und/oder Sitz mittels horizontaler Schwenkbolzen gelagert ist und Befestigungsteile mittels zweier in Ausnehmungen des Klosettbeckens eingreifender Schraubeneinrichtung befestigt sind ist zur Vereinfachung der Handhabung vorgesehen, daß die in Lageraugen des Deckels und/oder Sitzes eingreifenden Schwenkbolzen (1, 1', 1'') an den Befestigungsteilen (4, 4', 4'') mittels einer Verriegelungseinrichtung lösbar befestigt sind.

IPC 1-7

A47K 13/12

IPC 8 full level

A47K 13/12 (2006.01)

CPC (source: EP)

A47K 13/12 (2013.01)

Citation (search report)

- [X] US 4159548 A 19790703 - HEWSON CLIFFORD B
- [X] US 3613130 A 19711019 - SANSONE FRED A
- [Y] GB 2060019 A 19810429 - ICS CIDNEO SPA
- [Y] FR 2506595 A1 19821203 - ALLIBERT SA [FR]
- [Y] EP 0012791 A2 19800709 - STERNBERGER WALTER
- [Y] FR 2199816 A7 19740412 - BOSCH HAUSGERAETE GMBH [DE]
- [A] CH 348526 A 19600831 - SIEBENMANN & HEMMELER [CH]

Cited by

DE102014109277A1; GB2197418A; AT405125B; EP0856275A1; EP0635235A3; FR2703578A1; GB2289902A; GB2289902B; WO2016001318A1

Designated contracting state (EPC)

DE FR GB IT

DOCDB simple family (publication)

EP 0156967 A1 19851009; EP 0156967 B1 19890913; DE 3405350 A1 19850822; DE 3479701 D1 19891019

DOCDB simple family (application)

EP 84114232 A 19841124; DE 3405350 A 19840215; DE 3479701 T 19841124