

Title (en)  
METHOD FOR RESTORING RETAINING WALLS

Publication  
**EP 0157188 B1 19870616 (DE)**

Application  
**EP 85102385 A 19850304**

Priority  
DE 3408461 A 19840308

Abstract (en)  
[origin: EP0157188A1] 1. Method for the restoration of retaining walls with earth lying behind them by pressing in a mortar mass, characterised by the following process stages : a) at the foot of the retaining wall (1) at least one run-off drilling (5) and at a distance above this at least one flushing drilling (6) are drilled through the retaining wall ; b) through the flushing drilling (6) at least one flushing nozzle (9) is led into the area behind the retaining wall ; c) through the flushing nozzle (9) a cavity (12) at the rear side of the wall in the soil (2) is flushed out by means of high-pressure water-jets ; d) the rear side of the wall is cleaned by the high-pressure water jets ; e) the cavity (12) is filled by pressing in the mortar mass (14).

IPC 1-7  
**E02D 29/00**; **E02D 37/00**; **E04G 23/02**

IPC 8 full level  
**E02D 29/00** (2006.01); **E02D 29/02** (2006.01); **E02D 37/00** (2006.01); **E04G 23/02** (2006.01)

CPC (source: EP)  
**E02D 29/0275** (2013.01); **E02D 37/00** (2013.01); **E04G 23/0203** (2013.01); **E04G 23/0211** (2013.01)

Cited by  
DE10323141B4; DE102006018692A1; US6637981B2; WO9901631A1; WO2006088309A1; US6893192B2; US7011474B2

Designated contracting state (EPC)  
AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)  
**EP 0157188 A1 19851009**; **EP 0157188 B1 19870616**; AT E27839 T1 19870715; DE 3408461 A1 19850919; DE 3560264 D1 19870723

DOCDB simple family (application)  
**EP 85102385 A 19850304**; AT 85102385 T 19850304; DE 3408461 A 19840308; DE 3560264 T 19850304