

Title (en)  
SOCKET WITH AN INSULATION JACKET AND DEVICE FOR MAKING IT

Publication  
**EP 0158845 B2 19930623 (DE)**

Application  
**EP 85103143 A 19850319**

Priority  
DE 3410461 A 19840322

Abstract (en)  
[origin: EP0158845A2] 1. Connector socket for connector pins with a contact surface (9), which can be pressed against a connector pin, a conductor connection area (2) and a surrounding injection-moulded insulating sheath (20), the connector socket comprising a cylindrical, sleeve-shaped base member (1) between the contact surface (9) and the conductor connection area (2), characterised in that a partial surface (11) of the base member wall is bent into the base member cavity (13) about a bending line (12) extending approximately at a right angle to the plug-in axis (E) and bears via its entire edge (14) against the inner wall (15) of the base member cavity (13) as a locking disc.

IPC 1-7  
**H01R 43/24**; **H01R 13/405**

IPC 8 full level  
**H01R 13/405** (2006.01); **H01R 43/24** (2006.01); **H01R 13/05** (2006.01)

CPC (source: EP)  
**H01R 13/405** (2013.01); **H01R 43/24** (2013.01); **H01R 13/052** (2013.01)

Cited by  
EP0667056A4; CN111033905A; CN110838633A; EP0207310A3; EP0337400A3; DE19809706B4; EP1235305A3; DE102004034102A1; JPH0722479U; EP0866518A1; CN106229726A; US11050180B2; WO2019102827A1

Designated contracting state (EPC)  
DE FR GB IT NL

DOCDB simple family (publication)  
**EP 0158845 A2 19851023**; **EP 0158845 A3 19881005**; **EP 0158845 B1 19900207**; **EP 0158845 B2 19930623**; DE 3410461 A1 19850926; DE 3410461 C2 19870730; DE 3576019 D1 19900315; IE 56663 B1 19911023; IE 850719 L 19850922

DOCDB simple family (application)  
**EP 85103143 A 19850319**; DE 3410461 A 19840322; DE 3576019 T 19850319; IE 71985 A 19850321