

Title (en)

Process and device for the controlled advancing of under-ground pipes in inaccesible cross-sectional areas.

Title (de)

Verfahren und Vorrichtung zum gesteuerten unterirdischen Vortrieb von Rohren im unbegehbarer Durchmesserbereich.

Title (fr)

Procédé et dispositif pour la pose des conduites souterraines d'intérieur inaccessible par poussage contrôlé.

Publication

**EP 0159573 A1 19851030 (DE)**

Application

**EP 85103778 A 19850328**

Priority

DE 3412198 A 19840402

Abstract (en)

1. A process for the controlled underground advance of pipes (4) in the non-negotiable diameter range, comprising pressing forward a pipe line (4), starting from a starting excavation (1), with expansion or removal of the earth with a boring tool (15, 18), and possibly with the earth removed being conveyed to the starting excavation (1), characterized in that firstly, starting from the starting excavation (1), an encasing pipe line comprising encasing pipes (3, 3') which are of an inside diameter that is larger than the outside diameter of the product pipes (4) to be laid is advanced, possibly in addition with an outside seal (5), the boring tool (15) for boring through the earth is possibly withdrawn to the starting excavation (1) through the encasing pipe line (3, 3') which has been pressed forward thereto, and a boring tool (18) for boring through solid obstacles is pushed forward from the starting excavation (1) through the encasing pipe line (3, 3') and the obstacle is bored through, when the target object (2) is reached, if necessary after the boring tool in the encasing pipe line (3, 3') has been previously pulled back, a boring tool is pushed forward from the starting excavation to bore through the target object (2), said boring tool is withdrawn again to the starting excavation (1) after boring through the target object (2), then a product pipe line (4) is pushed forward from the starting excavation (1) through the encasing pipe line (3, 3') into the target object (2) and finally the encasing pipe line (3, 3') is withdrawn to the starting excavation (1), with the product pipe line (4) being fixed in position.

Abstract (de)

Bei diesem Verfahren wird zunächst von der Startgrube (1) ein Hüllrohrzug (3, 3') vorgetrieben. Das dabei eingesetzte Bohrwerkzeug für die Bodenbearbeitung kann gegebenenfalls zur Startgrube (1) zurückgezogen und zeitweilig durch ein Bohrwerkzeug zum Durchbohren fester Hindernisse ersetzt werden. Letzteres kann auch zum Durchbohren eines Zielobjektes (2) eingesetzt werden. Durch den Hüllrohrzug (3, 3') kann dann ein Produktenrohrzug (4) zum Zielobjekt (2) vorgeschoben werden. Der Hüllrohrzug (3, 3') kann unter Festhaltung des Produktenrohrzuges (4) zur Startgrube (1) zurückgezogen werden.

IPC 1-7

**E21B 7/20; E21B 10/32; E21B 7/04**

IPC 8 full level

**E21B 7/04** (2006.01); **E21B 7/20** (2006.01); **E21B 10/32** (2006.01)

CPC (source: EP)

**E21B 7/046** (2013.01); **E21B 7/20** (2013.01)

Citation (search report)

- [A] EP 0100748 A2 19840215 - BAUMANN & BURMEISTER [DE]
- [A] FR 2349091 A1 19771118 - GEWERK EISENHUETTE WESTFALIA [DE]
- [A] DE 2740473 A1 19790322 - GEWERK EISENHUETTE WESTFALIA
- [A] EP 0065284 A1 19821124 - NORTON CO [US]
- [A] DE 2422489 A1 19751120 - TAKECHI KOMUSHO KK
- [A] DE 3112172 A1 19821014 - HAUB FRANZ PETER
- [A] DE 3105916 A1 19820909 - GEWERK EISENHUETTE WESTFALIA [DE]
- [A] NL 7604193 A 19771025 - HELVOIRT C
- [A] NL 7905512 A 19810120 - RUITER TECH ADVIESBUREAU B V D
- [A] FR 2454572 A1 19801114 - ISEKI KAIHATSU KOKI [JP]

Cited by

US5655609A; GB2273142A; BE1006434A3; BE1003903A3; US5341888A; GB2252995A; GB2252995B; WO9109202A1; WO9413928A1; WO9720164A1

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI NL SE

DOCDB simple family (publication)

**EP 0159573 A1 19851030; EP 0159573 B1 19870930**; AT E30061 T1 19871015; DE 3412198 A1 19851010; DE 3560731 D1 19871105

DOCDB simple family (application)

**EP 85103778 A 19850328**; AT 85103778 T 19850328; DE 3412198 A 19840402; DE 3560731 T 19850328