

Title (en)

METHOD AND APPARATUS FOR THE LUBRICATION OF A CONTINUOUS-CASTING MOULD

Publication

**EP 0160635 B1 19890816 (FR)**

Application

**EP 85870056 A 19850424**

Priority

BE 6047961 A 19840427

Abstract (en)

[origin: EP0160635A2] In order to improve the lubrication of a mould (1) for the continuous casting of metal, in particular steel, at least one passage orifice (5) is made through the wall of the said mould, a lubricant is introduced via this orifice and the lubricant is caused to melt such that it spreads between the wall of the mould (1) and the metal (9). The lubricant may be in the form of a bar (6) consisting of a powder with a relatively low melting point; it may be subjected to a preheating and, if appropriate, to an onset of melting while in the passage orifice through the wall of the mould.  
<IMAGE>

IPC 1-7

**B22D 11/07**

IPC 8 full level

**B22D 11/07** (2006.01)

CPC (source: EP US)

**B22D 11/07** (2013.01 - EP US)

Cited by

EP0499563A1; FR2672524A1; EP0743114A1; FR2734186A1; US5682942A

Designated contracting state (EPC)

AT CH DE FR GB IT LI LU SE

DOCDB simple family (publication)

**BE 899544 A 19840816**; AT E45520 T1 19890915; DE 3572315 D1 19890921; EP 0160635 A2 19851106; EP 0160635 A3 19870603; EP 0160635 B1 19890816; JP S60247447 A 19851207; US 4917171 A 19900417

DOCDB simple family (application)

**BE 6047961 A 19840427**; AT 85870056 T 19850424; DE 3572315 T 19850424; EP 85870056 A 19850424; JP 9214885 A 19850426; US 72819385 A 19850429