

Title (en)

RAZOR HEAD WITH AN AUXILIARY FRAME

Publication

**EP 0161508 B1 19880427 (DE)**

Application

**EP 85104534 A 19850415**

Priority

- DE 3415122 A 19840421
- DE 3437141 A 19841010

Abstract (en)

[origin: EP0161508A1] 1. A dry shaving apparatus (4) having a movable lower cutter (1) and an upper cutter (2) which cooperates with the lower cutter (1) and is mounted in an auxiliary frame (3) provided with resilient detent means (32) on its end walls, characterized in that the auxiliary frame (3) is slidably insertable intermediate the end cheeks (9, 10) of a cutting head frame (18) or a shaver housing (4) in the direction of the lower cutter (1), that resilient detent means (32) having ascending ramps (33) are provided on the end walls (23, 24) of the auxiliary frame (3), that resilient release buttons (15) adapted to actuate the detent means (32) via the ascending ramps (33) are provided in the end cheeks (9, 10), and that the end cheeks (9, 10) provide above the release buttons (15) a recess (27) each including an abutment stop (28) for the detent means (32) of the auxiliary frame (3).

IPC 1-7

**B26B 19/38**

IPC 8 full level

**B26B 19/04** (2006.01); **B26B 19/38** (2006.01)

CPC (source: EP KR)

**B26B 19/00** (2013.01 - KR); **B26B 19/04** (2013.01 - EP); **B26B 19/38** (2013.01 - EP); **B26B 19/3853** (2013.01 - EP); **B26B 19/386** (2013.01 - EP)

Cited by

WO0005041A1; CN1071624C; FR2609924A1; CN114102680A; US5383273A; EP0320535A1; US6205666B1; US6329122B2; WO9806546A1; US6381849B2

Designated contracting state (EPC)

AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)

**EP 0161508 A1 19851121**; **EP 0161508 B1 19880427**; BR 8501890 A 19851224; DE 3562331 D1 19880601; HK 99690 A 19901207; KR 850007396 A 19851204; KR 930003934 B1 19930517; MX 160929 A 19900619; SG 83990 G 19910214

DOCDB simple family (application)

**EP 85104534 A 19850415**; BR 8501890 A 19850419; DE 3562331 T 19850415; HK 99690 A 19901129; KR 850002675 A 19850420; MX 20500385 A 19850417; SG 83990 A 19901015