

Title (en)

Flat key cylinder lock with anti-burglar features, particularly for use with master key locking systems.

Title (de)

Diebstahlsicheres Zylinderschloss, insbesondere für Systeme mit Haupt- und Nebenschlüsseln.

Title (fr)

Serrure cylindrique antivol, spécialement pour systèmes avec passe-partout.

Publication

EP 0161654 A2 19851121 (EN)

Application

EP 85105836 A 19850513

Priority

IT 346884 A 19840517

Abstract (en)

The present invention relates to a lock of the cylinder type, actuatable with a flat key, with antiburglar features. The cylinder lock comprises a plug (2) and auxiliary pins (9) which are disposed in seats (5), provided on the plugs (2) and arranged laterally to the channel (3) of introduction of the key. On introducing the key into the lock the pins (9) are displaced from their seats (5) such that, when the key is not the right one, they will engage into recesses (7) on the outer casing (1) of the lock, thus inhibiting rotation of the plug (2). By intervening on the pins it is also possible to obtain a set of hierarchically different locks for fabricating master key systems.

IPC 1-7

E05B 27/00; E05B 35/10

IPC 8 full level

E05B 27/00 (2006.01); **E05B 35/10** (2006.01)

CPC (source: EP)

E05B 27/0042 (2013.01); **E05B 27/0053** (2013.01)

Cited by

US5079936A; EP2905403A3; DE102004021580B3; US6526791B2; GB2387413A; GB2387413B; SE2350935A1; US8261587B2; WO02068780A1; US8746025B2; US8915107B2; WO2009147677A1; WO9725501A1; US11613909B1; US11542724B1; EP1593800A2; US11536047B1; WO2024041846A1

Designated contracting state (EPC)

AT BE CH DE FR GB LI NL SE

DOCDB simple family (publication)

EP 0161654 A2 19851121; **EP 0161654 A3 19860917**; **EP 0161654 B1 19900314**; **EP 0161654 B2 19940622**; AT E51052 T1 19900315; DE 3576546 D1 19900419; ES 543902 A0 19860616; ES 8607463 A1 19860616; IT 1179338 B 19870916; IT 8403468 A0 19840517

DOCDB simple family (application)

EP 85105836 A 19850513; AT 85105836 T 19850513; DE 3576546 T 19850513; ES 543902 A 19850517; IT 346884 A 19840517