

Title (en)  
**MULTIPLE PLUG**

Publication  
**EP 0163116 B1 19890118 (DE)**

Application  
**EP 85104905 A 19850423**

Priority  
DE 8413226 U 19840430

Abstract (en)  
[origin: US4659164A] A diode type connector having at least one solid guide pin inserted through an insulated housing, the pin having a front plug portion and a rear section for connection to a strand of a cable, the rear section having an axial concentric bore and a lateral slot located within the bore, and a connector terminal part having a connector part extending rearward for crimping onto the cable strand and a sleeve-like contact spring part having a length about that of the pin rear section and extending forward from engaging the pin rear section. The cable strand can either be soldered directly into the bore, or connected to the pin with the connector terminal part.

IPC 1-7  
**H01R 23/26**

IPC 8 full level  
**H01R 13/11** (2006.01); **H01R 24/38** (2011.01)

CPC (source: EP US)  
**H01R 24/00** (2013.01 - US); **H01R 24/38** (2013.01 - EP US); **Y10S 439/901** (2013.01 - EP US)

Designated contracting state (EPC)  
CH DE FR GB IT LI

DOCDB simple family (publication)  
**EP 0163116 A2 19851204; EP 0163116 A3 19870128; EP 0163116 B1 19890118**; DE 3567777 D1 19890223; DE 8413226 U1 19840802; IN 162170 B 19880409; JP S60236476 A 19851125; TR 22393 A 19870323; US 4659164 A 19870421

DOCDB simple family (application)  
**EP 85104905 A 19850423**; DE 3567777 T 19850423; DE 8413226 U 19840430; IN 315CA1985 A 19850426; JP 9130085 A 19850430; TR 2177185 A 19850430; US 72818685 A 19850429