

Title (en)
LUMINOUS DISPLAY DEVICE

Publication
EP 0165260 B1 19880727 (FR)

Application
EP 84904141 A 19841121

Priority
FR 8318776 A 19831123

Abstract (en)
[origin: WO8502478A1] Luminous display device comprising at least one front panel provided with a regular network of openings, each of which being associated to one end downstream of a light conductor and to a closing member controlled by an electromagnet, the upstream end of the light conductors being associated to a light source. It substantially comprises a closing member formed by a body (60) provided with an axial bore (71) intended to house the downstream end of a light conductor. Said body carries a stator (71) provided with energization coils (72) and a bipolar magnet (63) rotating about an axis (69). The bipolar magnet (63) is connected to a spherical bowl (76) susceptible of pivoting about the axis (69) between a closing position wherein the downstream end of the light conductor section is occulted and a lighting position wherein the downstream end of said light conductor appears as a luminous point in an opening of the front panel. Said device enables to display messages in a fixed, variable or continuously running mode.

IPC 1-7
G09F 9/37; **G09F 13/34**

IPC 8 full level
G09F 9/305 (2006.01); **G09F 9/37** (2006.01)

CPC (source: EP)
G09F 9/305 (2013.01); **G09F 9/375** (2013.01)

Citation (examination)
EP 0082975 A1 19830706 - MERK GMBH TELEFONBAU FRIED [DE]

Designated contracting state (EPC)
AT BE CH DE FR GB LI LU NL SE

DOCDB simple family (publication)
WO 8502478 A1 19850606; CA 1266973 A 19900327; DE 3473072 D1 19880901; EP 0165260 A1 19851227; EP 0165260 B1 19880727; FR 2555343 A1 19850524; FR 2555343 B1 19870123; IT 1178257 B 19870909; IT 8449194 A0 19841122; IT 8449194 A1 19860522

DOCDB simple family (application)
FR 8400269 W 19841121; CA 468475 A 19841123; DE 3473072 T 19841121; EP 84904141 A 19841121; FR 8318776 A 19831123; IT 4919484 A 19841122