

Title (en)

Trigger mechanism for small arms.

Title (de)

Abzugseinrichtung für Handfeuerwaffen.

Title (fr)

Dispositif de détente pour arme à feu individuelle.

Publication

EP 0165334 A1 19851227 (DE)

Application

EP 84107194 A 19840622

Priority

EP 84107194 A 19840622

Abstract (en)

1. Trigger device with a rear set trigger for small arms, in which there are arranged a trigger sear (2), pivotable in a housing (1), this trigger sear blocking the cocked firing pin in one of its pivot positions, a trigger rod (3) supporting the trigger sear in one of its pivot positions so as to hold it in its pivot position blocking the firing pin, a trigger (4) which, when operated in its trigger direction, pivots the trigger rod into its other pivot position releasing the trigger sear, and a pin cocking lever (5) which can be cocked by the trigger when it is operated counter to its trigger direction, wherein a safety element in its securing position prevents operation of the trigger in the trigger direction, characterized in that the trigger sear (2) is biased by a spring (8) into its pivot position blocking the cocked firing pin and is forced into its other pivot position by the released firing pin, in the latter pivot position restraining the pin cocking lever (5) in its released pivot position, in that when the trigger (4) is operated counter to the trigger direction it engages on the pin cocking lever (5), deflects this into the cocked position and retains it there in an unstable equilibrium, and in that the safety element (6) is a slide which, on being transferred from the released position to the securing position, disarms the cocked pin cocking lever (5), and which in its securing position blocks the trigger rod (3) against a release of the trigger sear (2) and blocks the trigger (4) against operation also in the direction counter to the trigger direction.

Abstract (de)

Eine Abzugseinrichtung mit Rückstecher für Handfeuerwaffen, bestehend aus einem Abzugsgehäuse, (1) einem Abzugsstollen (2), einer den Abzugsstollen abstützenden Abzugsstange (3), einem auf die Abzugsstange einwirkenden Abzug, (4) einem durch den Abzug spannbaren Stecherspannstück (5) und einem Sicherungselement (6) ihm von dem ungespannten Schlagbolzen aufgezwungenen Lage verhindert, daß das Stecherspannstück (5) mittels des Abzugs (4) gespannt werden kann und daß das Sicherungselement (6) in seiner gesicherten Stellung zum einen verhindert, daß die den Abzugsstollen (2) in seiner ihm von dem gespannten Schlagbolzen erlaubten anderen Lage haltenden Abzugsstange (3) aus der Stützrast des Abzugsstollens (2) ausgeschwenkt werden kann, und gleichzeitig auch verhindert, daß der Abzug (4) das Stecherspannstück (5) spannen kann. Damit wird erreicht, daß das Stecherspannstück (5) nur bei gespanntem Schlagbolzen und entsichertem Sicherungselement (6) gespannt werden kann und beim Überführen des Sicherungselements (6) aus der entsicherten in die sichernde Stellung selbsttätig wieder entspannt wird.

IPC 1-7

F41C 19/02; **F41C 17/00**

IPC 8 full level

F41A 17/56 (2006.01); **F41A 19/17** (2006.01)

CPC (source: EP)

F41A 17/56 (2013.01); **F41A 19/17** (2013.01)

Citation (search report)

- [AD] DE 2253199 A1 19740509 - SAUER & SOHN GMBH J
- [A] US 2856717 A 19581021 - PARKE WILLIAM R
- [AD] EP 0025518 A2 19810325 - KEPPLINGER JOHANN

Cited by

CN114688917A; EP0428292A3; US11015894B1; EP0408798A1; EP0533251A1; BE1005388A3; EP0534522A1; BE1005385A3; EP0515778A1; US5216190A; EP3748278A3

Designated contracting state (EPC)

AT CH DE FR GB IT LI SE

DOCDB simple family (publication)

EP 0165334 A1 19851227; **EP 0165334 B1 19880427**; AT E33899 T1 19880515; DE 3470801 D1 19880601

DOCDB simple family (application)

EP 84107194 A 19840622; AT 84107194 T 19840622; DE 3470801 T 19840622