

Title (en)
METHOD AND PLANT FOR COATING THE INTERIORS OF HOLLOW BODIES

Publication
EP 0167088 B1 19891227 (DE)

Application
EP 85107829 A 19850624

Priority
CH 326984 A 19840706

Abstract (en)
[origin: US4759946A] A method and an apparatus for interior coating of hollow bodies comprising a mandrel introducible into at least one tubular body, a coating arrangement on the mandrel for applying a coating medium to an interior of the tubular body and a heating mechanism on the mandrel and arranged so as to predominantly deliver heat directly from the mandrel into a surrounding area toward the tubular body. The heat-applying efficiency of burning in a coating medium can be improved by applying the heat from the interior at least predominantly directly to one of an interior area of the tubular body just before being coated and an interior area of the body already coated to burn in the coating according to the disclosed method.

IPC 1-7
B05B 5/08; **B05B 13/06**; **B05D 7/22**; **B21D 51/26**

IPC 8 full level
B05B 5/08 (2006.01); **B05B 5/12** (2006.01); **B05B 13/06** (2006.01); **B05C 7/02** (2006.01); **B05C 9/14** (2006.01); **B05D 1/04** (2006.01); **B05D 7/22** (2006.01); **B21D 51/26** (2006.01)

CPC (source: EP US)
B05B 5/12 (2013.01 - EP US); **B05B 13/0618** (2013.01 - EP US); **B05D 7/22** (2013.01 - EP US); **B21D 51/2676** (2013.01 - EP US); **B05D 3/0254** (2013.01 - EP US); **B05D 3/0263** (2013.01 - EP US); **B05D 7/222** (2013.01 - EP US)

Cited by
AU623370B2; EP0426258A1; DE4227455A1; WO8906165A1

Designated contracting state (EPC)
AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)
EP 0167088 A2 19860108; **EP 0167088 A3 19860910**; **EP 0167088 B1 19891227**; AT E48955 T1 19900115; DE 3574941 D1 19900201; JP H0659441 B2 19940810; JP S61107974 A 19860526; US 4759946 A 19880726

DOCDB simple family (application)
EP 85107829 A 19850624; AT 85107829 T 19850624; DE 3574941 T 19850624; JP 14812785 A 19850705; US 88910888 A 19880724