

Title (en)
METHOD OF AND APPARATUS FOR COATING OBJECTS, AND THEIR USE

Publication
EP 0170827 B1 19891227 (DE)

Application
EP 85107222 A 19850612

Priority
CH 342184 A 19840713

Abstract (en)
[origin: US4826704A] In order to increase the efficiency of a coating process wherein a coating medium such as, for example, powders directed from a coating medium pressure line toward a workpiece to be coated, with the coating process also including an applied electrostatic field, a coating medium which does not adhere to the workpiece is drawn off by way of a suction channel. A flow of the emerging coating medium is bent toward the workpiece that is to be coated by providing a carrier surface profile area between an outlet of the coating medium and a suction channel. By this arrangement a flow velocity gradient between the workpiece to be coated and the profile area is realized with the resulting pressure gradient from the profiled area toward the workpiece.

IPC 1-7
B05B 5/08; B05B 13/06; B05C 7/02; B05D 1/02

IPC 8 full level
B05B 5/08 (2006.01); **B05B 5/12** (2006.01); **B05B 13/06** (2006.01); **B05C 7/02** (2006.01); **B05D 1/02** (2006.01); **B05D 1/04** (2006.01); **B05D 1/12** (2006.01); **B05D 7/22** (2006.01)

CPC (source: EP US)
B05B 5/12 (2013.01 - EP US); **B05B 13/0618** (2013.01 - EP US); **B05C 7/02** (2013.01 - EP US); **B05D 1/12** (2013.01 - EP US); **B05D 7/222** (2013.01 - EP US)

Designated contracting state (EPC)
AT BE CH DE FR GB IT LI LU NL SE

DOCDB simple family (publication)
EP 0170827 A1 19860212; EP 0170827 B1 19891227; AT E48954 T1 19900115; CH 666630 A5 19880815; DE 3574940 D1 19900201; JP H069676 B2 19940209; JP S6133272 A 19860217; US 4826704 A 19890502

DOCDB simple family (application)
EP 85107222 A 19850612; AT 85107222 T 19850612; CH 342184 A 19840713; DE 3574940 T 19850612; JP 15500985 A 19850713; US 4981587 A 19870430