

Title (en)

CHIP VARISTOR FOR USE IN PRINTED CIRCUITS, AND METHOD OF PRODUCING IT

Publication

EP 0171642 B1 19880518 (DE)

Application

EP 85109001 A 19850718

Priority

DE 3428242 A 19840731

Abstract (en)

[origin: EP0171642A1] 1. A chip varistor for use in printed circuits (GS) for installation on conductor path contact surfaces (10, 11) of a printed circuit board (12), consisting of a parallelepiped-shaped ceramic body (20) of varistor material which is provided on oppositely disposed surfaces with solderable metal coatings (23, 24) as electrodes which extend at least on to that surface of the ceramic body (20) which faces towards the printed circuit board (12), characterized in that, at least on its side facing towards the printed circuit board (12), the ceramic body (20) is provided with a recess (25, 26) which forms two lateral parts (27, 28, 31, 32), that parts (35, 36, 37, 38) of the metal coatings (23, 24) extend to the end faces (29, 30, 33, 34) of the lateral parts (27, 28, 31, 32), and that the width and depth of the recess (25, 26) are such that the current path (41) along the surface parts of the recess (25, 26) between the ends (39, 40) of the parts (35, 36, 37, 38) of the metal coatings on the end faces (29, 30, 33, 34) of the lateral parts (27, 28, 31, 32) is longer than the lateral spacing (42) between the metal coatings (23, 24), which corresponds to the thickness of the ceramic body (20).

IPC 1-7

H01C 7/10

IPC 8 full level

H01C 7/10 (2006.01); **H01C 7/102** (2006.01)

CPC (source: EP)

H01C 7/102 (2013.01)

Cited by

FR2690003A1; EP0326212A1; EP0184645A3; DE3445698A1

Designated contracting state (EPC)

AT DE FR GB IT

DOCDB simple family (publication)

EP 0171642 A1 19860219; EP 0171642 B1 19880518; AT E34482 T1 19880615; DE 3562835 D1 19880623

DOCDB simple family (application)

EP 85109001 A 19850718; AT 85109001 T 19850718; DE 3562835 T 19850718